

# DS-7116NI-Q1/M

Hikvision NVR



## Specifications

Model	DS-7116NI-Q1/M
Brand	Hikvision
Növ	NVR
Kanal say?	16 kanal
Meqapixel	4 MP
Max HDD say?	1 HDD
Max HDD h?cmi	6 TB

---

**KEY FEATURES****Video and audio**

<b>IP video input</b>	<b>16 channels</b> <b>Resolution up to 4 MP</b>
<b>Input Bandwidth</b>	<b>40 Mbit/s</b>
<b>Output Bandwidth</b>	<b>60 Mbit/s</b>
<b>HDMI output</b>	<b>1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz</b>
<b>VGA output</b>	<b>1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz</b>
<b>Video output</b>	<b>Simultaneous HDMI/VGA output</b>

**Decoding**

<b>Decoding Format</b>	<b>H.265+ / H.265 / H.264+ / H.264</b>
<b>Recording permission</b>	<b>4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF</b>
<b>Synchronized playback</b>	<b>16 channels</b>
<b>Playback options</b>	<b>16 channels, @ 1080p (25 fps), 2 channels @ 4 MP (25 fps)</b>
<b>Stream type</b>	<b>Video, video and audio</b>

**Net**

<b>Remote connection</b>	<b>16</b>
<b>Network protocol</b>	<b>TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™</b>
<b>Network interface</b>	<b>1, RJ45 auto 10/100M Ethernet</b>

**Auxiliary Interfaces**

<b>SATA</b>	<b>1 SATA interface</b>
<b>Capacity</b>	<b>Up to 6 TB each drive</b>
<b>Alarm inputs/outputs</b>	<b>-</b>
<b>USB</b>	<b>Rear: 2 × USB 2.0</b>

**Basics**

<b>Nutrition</b>	<b>DC 12 V, 1.5 A</b>
<b>Power consumption (without HDD)</b>	<b>≤ 10 W</b>
<b>Working temperature</b>	<b>-10 to +55 °C</b>
<b>Operating humidity</b>	<b>From 10 to 90%</b>
<b>Dimensions</b>	<b>265 × 225 × 48 mm (10.4 × 8.9 × 1.9")</b>
<b>Weight (without storage)</b>	<b>≤ 1 kg</b>

**Certificates**

<b>FCC</b>	<b>Part 15 Subpart B, ANSI C63.4-2014</b>
<b>C.E.</b>	<b>EN50130-4, EN 61000-3-2, EN 61000-3-3</b>