

# DS-7116NI-Q1/M

## Hikvision NVR



Model	DS-7116NI-Q1/M
Brend	Hikvision
Növ	NVR
Kanal sayı	16 kanal
Meqapixel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	6 TB

## Specification

### Video and audio

IP video input	16 channels Resolution up to 4 MP
Input Bandwidth	40 Mbit/s
Output Bandwidth	60 Mbit/s
HDMI output	1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
VGA output	1 channel, 1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz
Video output	Simultaneous HDMI/VGA output

### Decoding

Decoding Format	H.265+ / H.265 / H.264+ / H.264
Recording permission	4 MP/3 MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronized playback	16 channels
Playback options	16 channels, @ 1080p (25 fps), 2 channels @ 4 MP (25 fps)
Stream type	Video, video and audio

### Net

Remote connection	16
Network protocol	TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™
Network interface	1, RJ45 auto 10/100M Ethernet

### Auxiliary Interfaces

SATA	1 SATA interface
Capacity	Up to 6 TB each drive
Alarm inputs/outputs	-
USB	Rear: 2 × USB 2.0

### Basics

Nutrition	DC 12 V, 1.5 A
Power consumption (without HDD)	≤ 10 W
Working temperature	-10 to +55 °C
Operating humidity	From 10 to 90%
Dimensions	265 × 225 × 48 mm (10.4 × 8.9 × 1.9")
Weight (without storage)	≤ 1 kg

## Certificates

FCC	Part 15 Subpart B, ANSI C63.4-2014
C.E.	EN50130-4, EN 61000-3-2, EN 61000-3-3