

# DS-7204HGHI-K1

## DS-7204HGHI-K1 DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7204HGHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	4 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	4 TB

## Specification

Motion Detection 2.0	
Human/Vehicle Analysis	<p>Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p> <p>Quick search by object or event typeis supported;</p>
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	<p>For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF</p> <p>For SD stream access:WD1/4CIF/VGA/CIF</p>
Frame Rate	<p>Main stream:</p> <p>For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@ 25fps (P)/30 fps (N)</p> <p>For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)</p> <p>Sub-stream:</p> <p>4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps (N)</p>
Video Bitrate	32 Kbps to 4Mbps

Stream Type	Video, Video &Audio
Audio Compression	G.711u
Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	1-ch (up to 5-ch) Up to 1080p resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog VideoInput	4-ch BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection
HDTV I Input	1080p25, 1080p30, 720p25,720p30
AHD Input	1080p25, 1080p30, 720p25,720p30
HDCVI Input	1080p25, 1080p30, 720p25,720p30
CVBS Input	Support
HDMI Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 × 720/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz
Video OutputMode	HDMI/VGA simultaneous output
Audio Input	1-ch RCA (2.0Vp-p, 1 KΩ) 4-ch viacoaxial cable
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	Reuse the firstaudio input
Synchronous playback	4-ch
Network	
Total Bandwidth	64 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
Remote Connection	32
Network Interface	1, RJ45 10/100Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 4 TB capacity for each disk
USB Interface	Rear panel:2 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC, 1.5 A
Consumption	≤ 16 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to +31 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	260 × 222 × 45 mm (10.2× 8.7 × 1.8 inch)
Weight	≤ 0.8 kg (without HDD, 1.8 lb.)