

# DS-7204HGHI-K1

## DS-7204HGHI-K1 DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7204HGHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	4 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	4 TB

## Specification

Motion Detection 2.0	
Human/Vehicle Analysis	<p>Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;</p> <p>Quick search by object or event typeis supported;</p>
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	<p>For 1080p streamaccess: 1080p Lite/720p Lite/WD1/4CIF/</p> <p>VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF</p> <p>For SD stream access:WD1/4CIF/VGA/CIF</p>

<b>Frame Rate</b>	<p>Main stream:</p> <p>For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/ CIF@25 fps(P)/30 fps (N) For 720p stream access: 720p/WD1/ 4CIF/VGA/CIF@ 25fps (P)/30 fps (N)</p> <p>For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)</p> <p>Sub-stream:</p> <p>4CIF@15fps; CIF/QVGA@25 fps (P)/30 fps (N)</p>
<b>Video Bitrate</b>	32 Kbps to 4Mbps
<b>Stream Type</b>	Video, Video & Audio
<b>Audio Compression</b>	G.711u
<b>Audio Bitrate</b>	64 Kbps
<b>Video and Audio</b>	
<b>IP Video Input</b>	<p>1-ch (up to 5-ch)</p> <p>Up to 1080p resolution</p> <p>Support H.265+/H.265/H.264+/H.264 IP cameras</p>
<b>Analog Video Input</b>	<p>4-ch</p> <p>BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection</p>
<b>HDTVI Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>AHD Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>HDCVI Input</b>	1080p25, 1080p30, 720p25, 720p30
<b>CVBS Input</b>	Support
<b>HDMI Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
<b>VGA Output</b>	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
<b>Video Output Mode</b>	HDMI/VGA simultaneous output
<b>Audio Input</b>	<p>1-ch RCA (2.0Vp-p, 1 KΩ)</p> <p>4-ch viacoaxial cable</p>
<b>Audio Output</b>	1-ch, RCA (Linear, 1 KΩ)
<b>Two-Way Audio</b>	Reuse the first audio input
<b>Synchronous playback</b>	4-ch
<b>Network</b>	
<b>Total Bandwidth</b>	64 Mbps
<b>Network Protocol</b>	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
<b>Remote Connection</b>	32
<b>Network Interface</b>	1, RJ45 10/100Mbps self-adaptive Ethernet interface
<b>Auxiliary Interface</b>	
<b>SATA</b>	1 SATA interface
<b>Capacity</b>	Up to 4 TB capacity for each disk
<b>USB Interface</b>	Rear panel: 2 × USB 2.0
<b>Alarm In/Out</b>	N/A
<b>General</b>	
<b>Power Supply</b>	12 VDC, 1.5 A
<b>Consumption</b>	≤ 16 W (without HDD)
<b>Working Temperature</b>	-10 °C to 55 °C (14 °F to +31 °F)
<b>Working Humidity</b>	10% to 90%

---

Dimension (W × D × H)	260 × 222 × 45 mm (10.2× 8.7 × 1.8 inch)
Weight	≤ 0.8 kg (without HDD, 1.8 lb.)