

# DS-7204HQHI-K1

## DS-7204HQHI-K1 4 AUDIO DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7204HQHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	4 kanal
Meqapixel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	10 TB

## Specification

	DS-7204HQHI-K1
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Analog video input	4-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTV input	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 Note: The 3 MP signal input is only available for channel 1 of DS-7204HQHI-K1, for channel 1/2 of DS-7208HQHI-K1, and for channel 1/2/3/4 of DS-7216HQHI-K1.
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
IP videoinput	1-ch (up to 5-ch) Up to 4 MP resolution Supports H.265+/H.265/H.264+/H.264 IP cameras
Audio compression	G.711u
Audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ)

CVBS output	1-ch, BNC(1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480
HDMI/VGA output	1-ch, 1920× 1080/60Hz, 1280× 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Encoding resolution	When 1080p Lite mode is not enabled: 4 MP lite/3 MP/1080p/720p/WD1/4CIF/VGA/CIF; When 1080p Lite mode is enabled: 4 MP lite/3MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF
Frame rate	Main stream: When 1080p Lite mode not enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p@15fps; 720p/VGA/WD1/4CIF/CIF@25fps(P)/30fps (N) For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: 4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)  Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)
Video bit rate	32 Kbps to 6 Mbps
Audio output	1-ch, RCA (Linear, 1 KΩ)
Audio bit rate	64 Kbps
Dual stream	Support
Stream type	Video, Video& Audio
Synchronous playback	4-ch
Remote connections	32
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
SATA	1 SATA interface
Capacity	Up to 10 TB capacity for each disk
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the 1st audio input)
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
USB interface	2 × USB 2.0
Serial interface	RS-485 (half-duplex)

Power supply	12 VDC
Consumption (without HDD)	≤ 6 W
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working humidity	10% to 90%
Dimensions (W x D x H)	315 x 242 x 45 mm(12.4 x 9.5 x 1.8 inch)
Weight (without HDD)	≤ 1.16 kg (2.6 lb)