

# DS-7204HQHI-K1/B

## HIKVISION DS-7204HQHI-K1/B Ballun TURBO HD DVR



Model	DS-7204HQHI-K1/B
Brend	Hikvision
Növ	XVR
Kanal sayı	4 kanal
Meqapixel	4 MP
Max HDD sayı	1 HDD
Max HDD həcmi	10 TB

## Specification

Model	DS-7204HQHI-K1/B
Recording	
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding resolution	<p>When 1080p Lite mode is not enabled: 4 MP lite/3 MP/1080p/720p/WD1/4CIF/VGA/CIF; When 1080p Lite mode is enabled: 4 MP lite/3 MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF</p>
Frame rate	<p>Main stream:</p> <p>When 1080p Lite mode is not enabled:</p> <p>For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)</p> <p>For 3 MP stream access: 3 MP/1080p/720p/VGA/WD1/4CIF/CIF@15fps For 1080p stream access: 1080p@15fps; 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps (N)</p> <p>For 720p stream access: 720p/VGA/WD1/4CIF/CIF@25fps (P)/30fps</p> <p>(N) When 1080p Lite mode is enabled: 4 MP lite/3 MP@15fps; 1080p lite/720p lite/VGA/WD1/4CIF/CIF@25fps(P)/ 30fps(N)</p>

<b>Sub-stream:</b>	
WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)	
Video bitrate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video & Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
<b>Video and Audio</b>	
IP videoinput	2-ch (up to 6-ch)
	Up to 6 MPresolution
	Support H.265+/H.265/H.264+/H.264 IP cameras
Analog videoinput	4-ch
	Balun interface, supporting coaxitron connection
HDTVI input	4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25 *: The 3 MP signal inputis only available for channel 1.
AHD input	4 MP25, 4 MP30, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	4 MP25, 4 MP30, 1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
CVBS output	1-ch, BNC (1.0 Vp-p, 75 Ω)
	Resolution: PAL:704 × 576, NTSC: 704 × 480
HDMI/VGA output	1-ch, 1920× 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz
Audio input	1-ch, RCA (2.0Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (usingthe first audioinput)
Synchronous playback	4-ch
<b>Network</b>	
Remote connections	32
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF
Network interface	1, RJ45 10M/100M self-adaptive Ethernet interface
<b>Auxiliary interface</b>	
SATA	1 SATA interface
Capacity	Up to 10 TB capacity for each disk
Serial interface	RS-485 (half-duplex)
USB interface	Rear panel: 2 × USB2.0
Alarm in/out	N/A
<b>General</b>	
Power supply	12 VDC
Consumption (without HDD)	≤ 6 W
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10% to 90%
Dimension (W × D × H)	260 × 222 × 45 mm(10.2 × 8.7 × 1.8 inch)
Weights (without HDD)	≤ 1.16 kg (2.6 lb)