

# DS-7208HGHI-K1

DS-7208HGHI-K1 DIGITAL VIDEO RECORDER HIKVISION



## Specifications

Model	DS-7208HGHI-K1
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	2 MP
Max HDD say?	1 HDD
Max HDD h?cmi	4 TB

## KEY FEATURES

## Motion Detection 2.0

Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;

Human/Vehicle Analysis Quick search by object or event type is supported;

## Recording

Video Compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF

For SD stream access: WD1/4CIF/VGA/CIF

## Encoding Resolution

Main stream:

For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps

For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream:

For 1080p and 720p stream access: CIF/QVGA@15 fps

For SD stream access: CIF/QVGA@25 fps (P)/30 fps (N)

## Frame Rate

Video Bitrate 32 Kbps to 4 Mbps

Stream Type Video, Video & Audio

Audio Compression G.711u

Audio Bitrate 64 Kbps

Video and Audio

2-ch (upto 10-ch)

Up to 5 MP resolution

IP Video Input Support H.265+/H.265/H.264+/H.264 IP cameras

8-ch

Analog Video Input BNC interface (1.0 Vp-p, 75 Ω), supporting coaxial connection

HDTVI Input 1080p25, 1080p30, 720p25, 720p30

AHD Input 1080p25, 1080p30, 720p25, 720p30

HDCVI Input 1080p25, 1080p30, 720p25, 720p30

CVBS Input Support

HDMI Output 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz

VGA Output 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz

Video Output Mode HDMI/VGA simultaneous output

---

	<b>1-ch RCA (2.0Vp-p, 1 K<math>\Omega</math>)</b>
<b>Audio Input</b>	<b>8-ch via coaxial cable</b>
<b>Audio Output</b>	<b>1-ch, RCA (Linear, 1 K<math>\Omega</math>)</b>
<b>Two-Way Audio</b>	<b>Reuse the first audio input</b>
<b>Synchronous playback</b>	<b>8-ch</b>
<b>Network</b>	
<b>Total Bandwidth</b>	<b>72 Mbps</b>
<b>Network Protocol</b>	<b>TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS</b>
<b>Remote Connection</b>	<b>64</b>
<b>Network Interface</b>	<b>1, RJ45 10/100Mbps self-adaptive Ethernet interface</b>
<b>Auxiliary Interface</b>	
<b>SATA</b>	<b>1 SATA interface</b>
<b>Capacity</b>	<b>Up to 4 TB capacity for each disk</b>
<b>USB Interface</b>	<b>Rear panel: 2 × USB 2.0</b>
<b>Alarm In/Out</b>	<b>N/A</b>
<b>General</b>	
<b>Power Supply</b>	<b>12 VDC, 1.5 A</b>
<b>Consumption</b>	<b>≤ 17 W (without HDD)</b>
<b>Working Temperature</b>	<b>-10 °C to 55 °C (14 °F to +31 °F)</b>
<b>Working Humidity</b>	<b>10% to 90%</b>
<b>Dimension (W × D × H)</b>	<b>260 × 222 × 45 mm (10.2 × 8.7 × 1.8 inch)</b>
<b>Weight</b>	<b>≤ 1 kg (without HDD, 2.2 lb.)</b>