

DS-7208HGHI-K1

DS-7208HGHI-K1 DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7208HGHI-K1
Brend	Hikvision
Növ	XVR
Kanal sayı	8 kanal
Meqapixel	2 MP
Max HDD sayı	1 HDD
Max HDD həcmi	4 TB

Specification

Motion Detection 2.0	
	Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;
Human/Vehicle Analysis	Quick search by object or event type is supported;
Recording	
Video Compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Encoding Resolution	For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF For 720p stream access: 720p/WD1/4CIF/VGA/CIF For SD stream access: WD1/4CIF/VGA/CIF
Frame Rate	Main stream: For 1080p stream access: 1080p Lite/720p Lite/WD1/4CIF/VGA/CIF@15 fps For 720p stream access: 720p/WD1/4CIF/VGA/CIF@15 fps For SD stream access: WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N) Sub-stream: For 1080p and 720p stream access: CIF/QVGA@15 fps For SD stream access: CIF/QVGA@25 fps (P)/30fps (N)
Video Bitrate	32 Kbps to 4 Mbps
Stream Type	Video, Video & Audio
Audio Compression	G.711u

Audio Bitrate	64 Kbps
Video and Audio	
IP Video Input	2-ch (upto 10-ch) Up to 5 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog Video Input	8-ch BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTVI Input	1080p25, 1080p30, 720p25, 720p30
AHD Input	1080p25, 1080p30, 720p25, 720p30
HDCVI Input	1080p25, 1080p30, 720p25, 720p30
CVBS Input	Support
HDMI Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Input	1-ch RCA (2.0Vp-p, 1 KΩ) 8-ch via coaxial cable
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	Reuse the first audio input
Synchronous playback	8-ch
Network	
Total Bandwidth	72 Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, UPnP™, HTTPS
Remote Connection	64
Network Interface	1, RJ45 10/100Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 4 TB capacity for each disk
USB Interface	Rear panel: 2 × USB 2.0
Alarm In/Out	N/A
General	
Power Supply	12 VDC, 1.5 A
Consumption	≤ 17 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to +31 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	260 × 222 × 45 mm (10.2 × 8.7 × 1.8 inch)
Weight	≤ 1 kg (without HDD, 2.2 lb.)