eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

DS-7208HTHI-K2

Kod: 00-00000447 · Videoregistrator



HIKVISION DS-7208HTHI-K2 TURBO HD DVR

Texniki göstəricilər

XVR	**8 kanal**
Növ	Kanal sayı
8 MP	**2 HDD**
Meqapixel	Max HDD sayı
10 TB	
Max HDD həcmi	

Ətraflı məlumat

	DS-7208HTHI-K2
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264
Analog video input	8-ch
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection
HDTVI input	8 MP, 5 MP,4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25
AHD input	5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	4 MP, 1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
IP videoinput	8-ch (up to 16-ch)
	Up to 8 MP resolution
	Supports H.265+/H.265/H.264+/H.264 IP cameras
Audio compression	G.711u
Audio input	4-ch, RCA (2.0 Vp-p,1 KΩ)
CVBS output	1-ch, BNC(1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480
HDMI/VGA output	**VGA**: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 ×720/60Hz, 1024 × 768/60Hz
	HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 ×720/60Hz, 1024 × 768/60Hz
Encoding resolution	8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF
Frame rate	Main stream: 8 MP@12fps, 5 MP@20fps, 3 MP@18fps 4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)
	Sub-stream: WD1/4CIF/CIF@25fps (P)/30fps (N)
Video bit rate	32 Kbps to 16 Mbps
Audio output	1-ch, RCA (Linear, 1 KΩ)

Audio bit rate	64 Kbps
Dual stream	Support
Stream type	Video, Video& Audio
Synchronous playback	8-ch
Incoming bandwidth	64 Mbps
Remote connections	64
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP,NFS, iSCSI, UPnP™,HTTPS, ONVIF
SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each disk
Two-way audio input	1-ch, RCA (2.0 Vp-p,1 KΩ) (using the 1st audio input)
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
USB interface	Front panel:1 × USB 2.0 Rear panel:1 × USB 3.0
Serial interface	RS-485 (half-duplex)
Alarm in/out	8/4
Power supply	12 VDC
Consumption (without HDD)	≤ 20 W
Working temperature	-10 °C to +55 °C (+14 °F to +131°F)
Working humidity	10% to 90%
Dimensions (W × D × H)	380 × 320 × 48 mm (15.0 × 12.6 × 1.9 inch)
Weight (without HDD)	≤ 2 kg (4.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az