

# DS-7208HTHI-K2

HIKVISION DS-7208HTHI-K2 TURBO HD DVR



## Specifications

Model	DS-7208HTHI-K2
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	8 MP
Max HDD say?	2 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

	<b>DS-7208HTHI-K2</b>
Video compression	<b>H.265 Pro+/H.265 Pro/H.265/H.264+/H.264</b>
Analog video input	<b>8-ch</b> <b>BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection</b>
HDTVI input	<b>8 MP, 5 MP, 4 MP, 3 MP, 1080p30, 1080p25, 720p60, 720p50, 720p30, 720p25</b>
AHD input	<b>5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30</b>
HDCVI input	<b>4 MP, 1080p25, 1080p30, 720p25, 720p30</b>
CVBS input	<b>PAL/NTSC</b> <b>8-ch (up to 16-ch)</b>
IP videoinput	<b>Up to 8 MP resolution</b> <b>Supports H.265+/H.265/H.264+/H.264 IP cameras</b>
Audio compression	<b>G.711u</b>
Audio input	<b>4-ch, RCA (2.0 Vp-p, 1 KΩ)</b>
CVBS output	<b>1-ch, BNC(1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480</b>
HDMI/VGA output	<b>VGA: 1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz</b> <b>HDMI: 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz</b>
Encoding resolution	<b>8 MP/5 MP/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF</b> <b>Main stream:</b>
Frame rate	<b>8 MP@12fps, 5 MP@20fps, 3 MP@18fps</b> <b>4 MP/1080p/720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)</b> <b>Sub-stream:</b> <b>WD1/4CIF/CIF@25fps (P)/30fps (N)</b>
Video bit rate	<b>32 Kbps to 16 Mbps</b>
Audio output	<b>1-ch, RCA (Linear, 1 KΩ)</b>
Audio bit rate	<b>64 Kbps</b>
Dual stream	<b>Support</b>
Stream type	<b>Video, Video&amp; Audio</b>
Synchronous playback	<b>8-ch</b>
Incoming bandwidth	<b>64 Mbps</b>
Remote connections	<b>64</b>
Network protocols	<b>TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP,NFS, iSCSI, UPnP™,HTTPS, ONVIF</b>

---

SATA	2 SATA interfaces
Capacity	Up to 10 TB capacity for each disk
Two-way audio input	1-ch, RCA (2.0 Vp-p, 1 K $\Omega$ ) (using the 1st audio input)
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
USB interface	Front panel: 1 $\times$ USB 2.0 Rear panel: 1 $\times$ USB 3.0
Serial interface	RS-485 (half-duplex)
Alarm in/out	8/4
Power supply	12 VDC
Consumption (without HDD)	$\leq$ 20 W
Working temperature	-10 $^{\circ}$ C to +55 $^{\circ}$ C (+14 $^{\circ}$ F to +131 $^{\circ}$ F)
Working humidity	10% to 90%
Dimensions (W $\times$ D $\times$ H)	380 $\times$ 320 $\times$ 48 mm (15.0 $\times$ 12.6 $\times$ 1.9 inch)
Weight (without HDD)	$\leq$ 2 kg (4.4 lb)