

DS-7208HUHI-M2/S

HIKVISION DS-7208HUHI-M2/S TURBO ACUSENSE DVR



| | |
|---------------|------------------|
| Model | DS-7208HUHI-M2/S |
| Brend | Hikvision |
| Növ | XVR |
| Kanal sayı | 8 kanal |
| Meqapixel | 8 MP |
| Max HDD sayı | 2 HDD |
| Max HDD həcmi | 10 TB |

Specification

| | |
|------------------------------|--|
| Motion Detection 2.0 | |
| | Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leavesand lights; |
| Human/Vehicle Analysis | Quick searchby object or event typeis supported; |
| Perimeter Protection | |
| Human/Vehicle Analysis | Up to 4-ch |
| Facial Detection | |
| Facial Detection and Capture | Face picturedetection, face picturesearch |
| Recording | |
| Video Compression | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 |
| Encoding Resolution | 8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF |

| | |
|-----------------------------|--|
| Frame Rate | <p>Main stream:</p> <p>8 MP@8 fps/3K@12 fps/5 MP@12fps/4 MP@15 fps/ 8MP Lite@15 fps/3MP@18 fps 1080p/720p/ WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N)</p> <p>Sub-stream:</p> <p>WD1/4CIF/CIF@25 fps (P)/30 fps (N)</p> |
| Video Bitrate | 32 Kbps to 10 Mbps |
| Dual-stream | Support |
| Stream Type | Video, Video &Audio |
| Audio Compression | G.711u |
| Audio Bitrate | 64 Kbps |
| Video and Audio | |
| IP Video Input | <p>4-ch (upto 12-ch)</p> <p>Up to 8 MP resolution Enhanced IP mode on:</p> <p>8-ch (up to 16-ch),each up to 4 Mbps</p> <p>Support H.265+/H.265/H.264+/H.264 IP cameras</p> |
| Analog VideoInput | 8-ch;BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection |
| HDMI Output | <p>HDMI:</p> <p>1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz</p> <p>VGA:</p> <p>1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz</p> <p>HDMI/VGA simultaneous output</p> |
| CVBS Input | PAL/NTSC |
| CVBS Output | <p>1-ch, BNC (1.0 Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC:704 × 480</p> |
| Synchronous playback | 8-ch |
| HDTVI Input | <p>8 MP(3840× 2160)@15 fps, 8 MP(3840× 2160)@12 fps, 3K(2960 x 1665)@20 fps, 5 MP(2560 × 1944)@20 fps, 5 MP(2560× 1944)@12 fps, 4 MP(2560× 1440)@30 fps, 4 MP(2560 × 1440)@25 fps, 3 MP@18 fps,1080p@30 fps, 1080p@25 fps,720p@30 fps, 720p@25 fps</p> |
| AHD Input | <p>5 MP(2560 × 1944)@20 fps, 5 MP(2560 × 1944)@12 fps, 4 MP(2560 × 1440)@30 fps, 4 MP(2560 × 1440)@25 fps, 1080p@30 fps,1080p@25 fps, 720p@30fps, 720p@25 fps</p> |

| | |
|------------------------------|---|
| HDCVI Input | 8 MP(3840× 2160)@15 fps, 8 MP(3840 × 2160)@12 fps, 5 MP(2592 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps, 4 MP(2560× 1440)@25 fps, 1080p@30 fps, 1080p@25 fps, 720p@30 fps, 720p@25 fps |
| Audio Output | 1-ch, RCA (Linear, 1 KΩ) |
| Audio Input | 1-ch, RCA (2.0 Vp-p, 1 KΩ) |
| Two-Way Audio | 1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audioinput) |
| Network | |
| Total Bandwidth | 128Mbps |
| Network Protocol | TCP/IP, PPPoE,DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™,HTTPS, ONVIF |
| Remote Connection | 64 |
| Network Interface | 1,RJ45 10M/100M/1000M self-adaptive Ethernet interface |
| Auxiliary Interface | |
| SATA | 2 SATA interface |
| Capacity | Up to 10 TBcapacity for each disk |
| Serial Interface | RS-485 (half-duplex) |
| USB Interface | 1 × USB 2.0 1 × USB 3.0 |
| Alarm In/Out | N/A |
| General | |
| Power Supply | 12 VDC |
| Consumption | ≤ 15 W |
| Working Temperature | -10 °C to +55 °C (+14 °F to +131 °F) |
| Working Humidity | 10% to 90% |
| Dimension (W × D × H) | 380 × 320 × 48 mm (15.0× 12.6 × 1.9 inch) |
| Weight | ≤ 2 kg (4.4 lb) |