

DS-7208HUHI-M2/S

HIKVISION DS-7208HUHI-M2/S TURBO ACUSENSE DVR



Specifications

Model	DS-7208HUHI-M2/S
Brand	Hikvision
Növ	XVR
Kanal say?	8 kanal
Meqapixel	8 MP
Max HDD say?	2 HDD
Max HDD h?cmi	10 TB

KEY FEATURES

Motion Detection 2.0

Deep learning-based motion detection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leaves and lights;

Human/Vehicle Analysis

Quick search by object or event type is supported;

Perimeter Protection

Human/Vehicle Analysis Up to 4-ch

Facial Detection

Facial Detection and Capture Face picture detection, face picture search

Recording

Video Compression H.265 Pro+/H.265 Pro/H.265/H.264+/H.264

Encoding Resolution 8 MP/5 MP/3K/4 MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF

Main stream:

8 MP@8 fps/3K@12 fps/5 MP@12fps/4 MP@15 fps/

8MP Lite@15 fps/3MP@18 fps 1080p/720p/

Frame Rate

WD1/4CIF/VGA/CIF@25 fps(P)/30 fps (N)

Sub-stream:

WD1/4CIF/CIF@25 fps (P)/30 fps (N)

Video Bitrate

32 Kbps to 10 Mbps

Dual-stream

Support

Stream Type

Video, Video & Audio

Audio Compression

G.711u

Audio Bitrate

64 Kbps

Video and Audio

4-ch (upto 12-ch)

Up to 8 MP resolution Enhanced IP mode on:

8-ch (up to 16-ch), each up to 4 Mbps

IP Video Input

Support H.265+/H.265/H.264+/H.264 IP cameras

Analog Video Input

8-ch; BNC interface (1.0Vp-p, 75 Ω), supporting coaxitron connection

	HDMI:
	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz,
	1920 × 1080/60Hz,
	1280 × 1024/60Hz,
	1280 × 720/60Hz VGA:
	1-ch, 1920 × 1080/60Hz,
	1280 × 1024/60Hz,
HDMI Output	1280 × 720/60Hz
	HDMI/VGA simultaneous output
CVBS Input	PAL/NTSC
	1-ch, BNC (1.0 Vp-p, 75 Ω),
CVBS Output	resolution: PAL: 704 × 576, NTSC: 704 × 480
Synchronous playback	8-ch
	8 MP(3840× 2160)@15 fps, 8 MP(3840× 2160)@12 fps,
	3K(2960 x 1665)@20 fps, 5 MP(2560 × 1944)@20 fps,
HDTVI Input	5 MP(2560× 1944)@12 fps, 4 MP(2560× 1440)@30 fps,
	4 MP(2560 × 1440)@25 fps, 3 MP@18 fps, 1080p@30 fps,
	1080p@25 fps, 720p@30 fps, 720p@25 fps
	5 MP(2560 × 1944)@20 fps, 5 MP(2560 × 1944)@12 fps,
AHD Input	4 MP(2560 × 1440)@30 fps, 4 MP(2560 × 1440)@25 fps,
	1080p@30 fps, 1080p@25 fps, 720p@30fps, 720p@25 fps
HDCVI Input	8 MP(3840× 2160)@15 fps, 8 MP(3840 × 2160)@12 fps,
	5 MP(2592 × 1944)@20 fps, 4 MP(2560 × 1440)@30 fps,
	4 MP(2560× 1440)@25 fps, 1080p@30 fps, 1080p@25 fps,
	720p@30 fps, 720p@25 fps
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ) (using the first audioinput)
Network	
Total Bandwidth	128Mbps
Network Protocol	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS,
	iSCSI, UPnP™, HTTPS, ONVIF
Remote Connection	64
Network Interface	1, RJ45 10M/100M/1000M self-adaptive