

# DS-7332HQHI-K4



Model	DS-7332HQHI-K4
Brend	Hikvision
Növ	XVR
Kanal sayı	32 kanal
Meqapixel	4 MP
Max HDD sayı	4 HDD
Max HDD həcmi	10 TB

## Specification

Model	DS-7324HQHI-K4	DS-7332HQHI-K4
Recording		
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
Encoding resolution	When 1080p Litemode not enabled: 4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF When 1080p Lite mode enabled: 4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF	

Frame rate	<p><b>Main stream:</b></p> <p><b>When 1080pLite mode not enabled:</b></p> <p>For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/ CIF@25fps (P)/30fps (N)</p> <p>For 3 MP stream access: 3 MP/1080p/720p/WD1/4CIF/VGA/CIF@15fps</p> <p>For 1080p stream access: 1080p/720p@15fps; WD1/4CIF/VGA/CIF@25fps (P) /30fps (N)</p> <p>For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N)</p> <p><b>When 1080pLite mode enabled:</b></p> <p>For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p lite/WD1/4CIF/ VGA/CIF@25fps (P)/30fps (N)</p> <p>For 3 MP stream access: 3 MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF@15fps For 1080p stream access: 1080p lite/720p lite/ WD1/4CIF/VGA/CIF@25fps (P)</p> <p>/30fps (N)</p> <p>For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps(P)/30fps (N)</p>	
	<p><b>Sub-stream:</b></p> <p>WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)</p>	
Video bitrate	32 Kbps to 6 Mbps	
Dual stream	Support	
Stream type	Video, Video & Audio	
Audio compression	G.711u	
Audio bit rate	64 Kbps	
Video and Audio		
IP video input	16-ch (up to 40-ch)	16-ch (up to 48-ch)
	Up to 6 MP resolution	
	Support H.265+/H.265/H.264+/H.264 IP cameras	
Analog video input	24-ch	32-ch
	BNC interface (1.0 Vp-p, 75 Ω), supporting coaxitron connection	
HDTVI input	4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 *: The 3 MP signal input is only available for channel 1/2/3/4.	
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30	
HDCVI input	1080p25, 1080p30, 720p25, 720p30	
CVBS input	PAL/NTSC	
CVBS output	1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL: 704 × 576, NTSC: 704 × 480	
HDMI1/VGA output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	
HDMI2 output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz	

Audio input	4-ch, RCA (2.0Vp-p, 1 K $\Omega$ )
Audio output	1-ch, RCA (Linear, 1 K $\Omega$ )
Two-way audio	1-ch, RCA (2.0 Vp-p,1 K $\Omega$ ) (independent)
Synchronous playback	16-ch
Network	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP,Hik-Connect, DNS, DDNS,NTP, SADP, NFS,iSCSI, UPnP™, HTTPS, ONVIF,SNMP
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary interface	
SATA	4 SATA interfaces
eSATA	Support
Capacity	Up to 10 TB capacity for each disk
Serial interface	RS-232, RS-485 (full-duplex), Keyboard
Alarm in/out	16/4
USB interface	Front panel:2 × USB 2.0 Rear panel:1 × USB 3.0
General	
Power supply	100 to 240 VAC, 50 to 60 Hz, 1.1 A
Consumption (without HDD)	≤ 45 W
Working temperature	-10 °C to +55 °C (+14 °F to+131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	440 × 390 × 70 mm (17.3 × 15.4 × 2.8 inch)
Weights (without HDD)	≤ 7 kg (15.4 lb)