eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

DS-7332HQHI-K4

Kod: 00-00002658 · Videoregistrator



Hikvision DS-7332HQHI-K4 — texniki göstəricilər aşağıda verilib.

Texniki göstəricilər

XVR	Növ
32 kanal	Kanal sayı
4 MP	Meqapixel
4 HDD	Max HDD sayı
10 TB	Max HDD həcmi

Ətraflı məlumat

Model	DS-7324HQHI-K4	DS-7332HQHI-K4
Recording		
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
Encoding resolution	When 1080p Litemode not enabled: 4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF When1080p Lite mode enabled: 4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF	
Frame rate	Main stream: When 1080pLite mode not enabled: For 4 MP stream access:4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/ CIF@25fps (P)/30fps (N) For 3 MP streamaccess: 3 MP/1080p/720p/WD1/4CIF/VGA/CIF@15fps For 1080p stream access: 1080p/720p@15fps; WD1/4CIF/VGA/CIF@25fps (P) /30fps (N) For 720p streamaccess: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) When 1080pLite mode enabled: For 4 MP stream access:4 MP lite@15fps; 1080p lite/720p lite/WD1/4CIF/ VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF@15fps For 1080p stream access:1080p lite/720p lite/ WD1/4CIF/VGA/CIF@25fps (P) /30fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps(P)/30fps (N)	
	Sub-stream: WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)	

Video bitrate	32 Kbps to 6 Mbps	
Dual stream	Support	
Stream type	Video, Video &Audio	
Audio compression	G.711u	
Audio bit rate	64 Kbps	
Video and Audio		
IP video input	16-ch (up to 40-ch)	16-ch (up to 48-ch)
	Up to 6 MP resolution	
	Support H.265+/H.265/H.264+/H.264 IP cameras	
Analog videoinput	24-ch	32-ch
	BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection	
HDTVI input	4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 ***: The 3 MP signal inputis only available for channel 1/2/3/4.**	
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30	
HDCVI input	1080p25, 1080p30, 720p25,720p30	
CVBS input	PAL/NTSC	
CVBS output	1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL:704 × 576, NTSC: 704× 480	
HDMI1/VGA output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz	
HDMI2 output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280× 720/60Hz, 1024 × 768/60Hz	

Audio input	4-ch, RCA (2.0Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p,1 KΩ) (independent)
Synchronous playback	16-ch
Network	
Remote connections	128

Network protocols	TCP/IP, PPPoE, DHCP,Hik-Connect, DNS, DDNS,NTP, SADP, NFS,iSCSI, UPnP™, HTTPS, ONVIF,SNMP
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary interface	
SATA	4 SATA interfaces
eSATA	Support
Capacity	Up to 10 TB capacity for each disk
Serial interface	RS-232, RS-485 (full-duplex), Keyboard
Alarm in/out	16/4
USB interface	Front panel:2 × USB 2.0 Rear panel:1 × USB 3.0
General	
Power supply	100 to 240 VAC, 50 to 60 Hz, 1.1 A
Consumption (without HDD)	≤ 45 W
Working temperature	-10 °C to +55 °C (+14 °F to+131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	440 × 390 × 70 mm (17.3 × 15.4 × 2.8 inch)
Weights (without HDD)	≤ 7 kg (15.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az