

DS-7332HQHI-K4

NVR for IP Cameras



Specifications

| | |
|---------------|----------------|
| Model | DS-7332HQHI-K4 |
| Brand | Hikvision |
| Növ | XVR |
| Kanal say? | 32 kanal |
| Meqapixel | 4 MP |
| Max HDD say? | 4 HDD |
| Max HDD h?cmi | 10 TB |

KEY FEATURES

| | | |
|----------------------------|---|-----------------------|
| Model | DS-7324HQHI-K4 | DS-7332HQHI-K4 |
| Recording | | |
| Video compression | H.265 Pro+/H.265 Pro/H.265/H.264+/H.264 | |
| | When 1080p Litemode not enabled: | |
| | 4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF | |
| | When 1080p Lite mode enabled: | |
| Encoding resolution | 4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF | |
| | Main stream: | |
| | When 1080p Lite mode not enabled: | |
| | For 4 MP stream access: 4 MP lite@15fps; | |
| | 1080p lite/720p/WD1/4CIF/VGA/ CIF@25fps (P)/30fps (N) | |
| | For 3 MP stream access: 3 MP/1080p/720p/WD1/4CIF/VGA/CIF@15fps | |
| | For 1080p stream access: 1080p/720p@15fps; WD1/4CIF/VGA/CIF@25fps (P) | |
| | /30fps (N) | |
| | For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) | |
| | When 1080p Lite mode enabled: | |
| | For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p lite/WD1/4CIF/ | |
| Frame rate | VGA/CIF@25fps (P)/30fps (N) | |
| | For 3 MP stream access: 3 MP/1080p lite/720p | |
| | lite/WD1/4CIF/VGA/CIF@15fps For 1080p stream access: 1080p lite/720p lite/ | |
| | WD1/4CIF/VGA/CIF@25fps (P) | |
| | /30fps (N) | |
| | For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps(P)/30fps (N) | |
| | Sub-stream: | |
| | WD1/4CIF@12fps; CIF@25fps (P)/30fps (N) | |
| Video bitrate | 32 Kbps to 6 Mbps | |
| Dual stream | Support | |
| Stream type | Video, Video & Audio | |
| Audio compression | G.711u | |
| Audio bit rate | 64 Kbps | |

Video and Audio

| | | |
|------------------------|--|---------------------|
| | 16-ch (up to 40-ch) | 16-ch (up to 48-ch) |
| IP video input | Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras | |
| | 24-ch | 32-ch |
| Analog videoinput | BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection | |
| | 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 | |
| HDTVl input | *: The 3 MP signal inputis only available for channel 1/2/3/4. | |
| AHD input | 4 MP, 1080p25, 1080p30, 720p25, 720p30 | |
| HDCVl input | 1080p25, 1080p30, 720p25,720p30 | |
| CVBS input | PAL/NTSC | |
| CVBS output | 1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL:704 × 576, NTSC: 704× 480 | |
| HDMI1/VGA output | 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz | |
| | 1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × | |
| HDMI2 output | 1024/60Hz, 1280× 720/60Hz, 1024 × 768/60Hz | |
| Audio input | 4-ch, RCA (2.0Vp-p, 1 KΩ) | |
| Audio output | 1-ch, RCA (Linear, 1 KΩ) | |
| Two-way audio | 1-ch, RCA (2.0 Vp-p,1 KΩ) (independent) | |
| Synchronous playback | 16-ch | |
| Network | | |
| Remote connections | 128 | |
| | TCP/IP, PPPoE, DHCP,Hik-Connect, DNS, DDNS,NTP, SADP, NFS,iSCSI, UPnP™, | |
| Network protocols | HTTPS, ONVIF,SNMP | |
| Network interface | 1, RJ45 10M/100M/1000M self-adaptive Ethernet interface | |
| Auxiliary interface | | |
| SATA | 4 SATA interfaces | |
| eSATA | Support | |
| Capacity | Up to 10 TB capacity for each disk | |
| Serial interface | RS-232, RS-485 (full-duplex), Keyboard | |
| Alarm in/out | 16/4 | |
| | Front panel:2 × USB 2.0 | |
| USB interface | Rear panel:1 × USB 3.0 | |
| General | | |
| Power supply | 100 to 240 VAC, 50 to 60 Hz, 1.1 A | |
| Consumption | | |
| (without HDD) | ≤ 45 W | |
| Working temperature | -10 °C to +55 °C (+14 °F to+131 °F) | |
| Working humidity | 10% to 90% | |
| Dimensions (W × D × H) | 440 × 390 × 70 mm (17.3 × 15.4 × 2.8 inch) | |
| Weights (without HDD) | ≤ 7 kg (15.4 lb) | |