

# DS-7332HQHI-K4



Model	DS-7332HQHI-K4
Brend	Hikvision
Növ	XVR
Kanal sayı	32 kanal
Meqapixel	4 MP
Max HDD sayı	4 HDD
Max HDD həcmi	10 TB

## Specification

Model	DS-7324HQHI-K4	DS-7332HQHI-K4
Recording		
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
Encoding resolution	<p>When 1080p Lite mode not enabled: 4 MP lite/3 MP/1080p/1080p lite/720p/WD1/4CIF/VGA/CIF When 1080p Lite mode enabled: 4 MP lite/3 MP/1080p lite/720p/720p lite/WD1/4CIF/VGA/CIF</p>	
Frame rate	<p><b>Main stream:</b> When 1080p Lite mode not enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p/WD1/4CIF/VGA/ CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p/720p/WD1/4CIF/VGA/CIF@15fps For 1080p stream access: 1080p/720p@15fps; WD1/4CIF/VGA/CIF@25fps (P) /30fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps (P)/30fps (N) When 1080p Lite mode enabled: For 4 MP stream access: 4 MP lite@15fps; 1080p lite/720p lite/WD1/4CIF/ VGA/CIF@25fps (P)/30fps (N) For 3 MP stream access: 3 MP/1080p lite/720p lite/WD1/4CIF/VGA/CIF@15fps For 1080p stream access: 1080p lite/720p lite/ WD1/4CIF/VGA/CIF@25fps (P) /30fps (N) For 720p stream access: 720p/WD1/4CIF/VGA/CIF@25fps(P)/30fps (N)</p>	

<b>Sub-stream:</b>	
WD1/4CIF@12fps; CIF@25fps (P)/30fps (N)	
Video bitrate	32 Kbps to 6 Mbps
Dual stream	Support
Stream type	Video, Video &Audio
Audio compression	G.711u
Audio bit rate	64 Kbps
<b>Video and Audio</b>	
IP video input	16-ch (up to 40-ch)
	16-ch (up to 48-ch)
	Up to 6 MP resolution Support H.265+/H.265/H.264+/H.264 IP cameras
Analog videoinput	24-ch
	32-ch BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection
HDTVI input	4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60 *: The 3 MP signal inputis only available for channel 1/2/3/4.
AHD input	4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	1080p25, 1080p30, 720p25,720p30
CVBS input	PAL/NTSC
CVBS output	1-ch, BNC (1.0Vp-p, 75 Ω), resolution: PAL:704 × 576, NTSC: 704× 480
HDMI1/VGA output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz
HDMI2 output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280× 720/60Hz, 1024 × 768/60Hz

Audio input	4-ch, RCA (2.0Vp-p, 1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0 Vp-p,1 KΩ) (independent)
Synchronous playback	16-ch
<b>Network</b>	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP,Hik-Connect, DNS, DDNS,NTP, SADP, NFS,iSCSI, UPnP™, HTTPS, ONVIF,SNMP
Network interface	1, RJ45 10M/100M/1000M self-adaptive Ethernet interface
<b>Auxiliary interface</b>	
SATA	4 SATA interfaces
eSATA	Support
Capacity	Up to 10 TB capacity for each disk
Serial interface	RS-232, RS-485 (full-duplex), Keyboard
Alarm in/out	16/4
USB interface	Front panel:2 × USB 2.0 Rear panel:1 × USB 3.0
<b>General</b>	
Power supply	100 to 240 VAC, 50 to 60 Hz, 1.1 A
Consumption (without HDD)	≤ 45 W
Working temperature	-10 °C to +55 °C (+14 °F to+131 °F)

Working humidity	10% to 90%
Dimensions (W x D x H)	440 x 390 x 70 mm (17.3 x 15.4 x 2.8 inch)
Weights (without HDD)	≤ 7 kg (15.4 lb)