eurotech
Taste of technology

TEXNIKI SƏNƏD

29.11.2026

HIKVISION

DS-7332HUHI-K4

Kod: 00-00002659 · Videoregistrator



Hikvision DS-7332HUHI-K4 — texniki göstəricilər aşağıda verilib.

Texniki göstəricilər

XVR	Növ
32 kanal	Kanal sayı
8 MP	Meqapixel
4 HDD	Max HDD sayı
10 TB	Max HDD həcmi

Ətraflı məlumat

Model	DS-7324HUHI-K4	DS-7332HUHI-K4
Perimeter Protection[1]		
Line crossing detection/intrusion detection	2-ch Enhanced VCA mode on: 24-ch	2-ch Enhanced VCA mode on: 32-ch
Recording		
Video compression	H.265 Pro+/H.265 Pro/H.265/H.264+/H.264	
Encoding resolution	8 MP/5 MP/4MP/3 MP/1080p/720p/WD1/4CIF/VGA/CIF	
Frame rate	Main stream: 8 MP@8fps/5 MP@12 fps;4 MP@15 fps;3 MP@18 fps; 1080p/720p/WD1/4CIF/VGA/CIF@25 fps (P)/30 fps (N)	
	Sub-stream: WD1/4CIF/CIF@25 fps(P)/30 fps (N)	
Video bit rate	32 Kbps to 10 Mbps	
Dual stream	Support	
Stream type	Video, Video & Audio	
Audio compression	G.711u	
Audio bit rate	64 Kbps	
Video andAudio		
IP videoinput	16-ch (up to 40-ch)	16-ch (up to 48-ch)
	Up to 8 MP resolution	
	Support H.265+/H.265/H.264+/H.264 IP cameras	
Analog videoinput	24-ch	32-ch
	BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection	

HDTVI input	8 MP, 5 MP, 4 MP, 3 MP, 1080p25, 1080p30, 720p25, 720p30, 720p50, 720p60
AHD input	5 MP, 4 MP, 1080p25, 1080p30, 720p25, 720p30
HDCVI input	4 MP, 1080p25, 1080p30, 720p25, 720p30
CVBS input	PAL/NTSC
CVBS output	1-ch, BNC (1.0Vp-p, 75 Ω),resolution: PAL: 704 × 576,NTSC: 704 × 480
HDMI1/VGA output	1-ch, 1920× 1080/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz
HDMI2 output	1-ch, 4K (3840× 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920× 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Audio input	4-ch, RCA (2.0 Vp-p,1 KΩ)
Audio output	1-ch, RCA (Linear, 1 KΩ)
Two-way audio	1-ch, RCA (2.0Vp-p, 1 KΩ) (independent)
Synchronous playback	16-ch
Network	
Remote connections	128
Network protocols	TCP/IP, PPPoE, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, NFS, iSCSI, UPnP™, HTTPS, ONVIF, SNMP
Network interface	2, RJ45 10M/100M/1000M self-adaptive Ethernet interface
Auxiliary interface	

SATA	4 SATA interfaces
eSATA	Support
Capacity	Up to 10 TB capacity for each disk
Serial interface	RS-232, RS-485 (full-duplex), Keyboard
Alarm in/out	16/4

USB interface	Front panel: 2 × USB 2.0 Rear panel:1 × USB 3.0
General	
Power supply	100 to 240 VAC,50 to 60 Hz, 1.3 A
Consumption **(without HDD)**	≤ 74 W
Working temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Working humidity	10% to 90%
Dimensions (W × D × H)	440 × 390 × 70 mm(17.3 × 15.4× 2.8 inch)
Weights (without HDD)	≤ 7 kg (15.4 lb)

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az