HIKVISION

DS-7604NI-K1/4P

Kod: 00-00001134 · Videoregistrator



DS-7604NI-K1 4P POE NETWORK DIGITAL VIDEO RECORDER HIKVISION

Texniki göstəricilər

NVR Növ	**4 kanal** Kanal sayı
8 MP Meqapixel	**1 HDD** Max HDD sayı
8 TB Max HDD həcmi	

Ətraflı məlumat

Motion Detection 2.0	
Human/Vehicle Analysis	1-ch
Video and Audio	
IP Video Input	4-ch
Incoming Bandwidth	40 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz,1280 x 720/60Hz
VGA Output	1-ch, 1920× 1080/60 Hz, 1280 × 1024/60 Hz,1280 × 720/60 Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA(2.0 Vp-p, 1kΩ)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	4-ch
Decoding Capability	1-ch@8 MP (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps) *: The length or width of camera resolution (each track) cannotexceed 4096 pixels.
Stream Type	Video, Video& Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726
Network	
Remote Connection	32

Network Protocol	TCP/IP, DHCP, IPv4, IPv6,DNS, DDNS, NTP, RTSP, SADP,SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP,HTTPS
Network Interface	1 RJ-45 10 /100Mbps self-adaptive Ethernet interface
Auxiliary Interface	
SATA	1 SATA interface
Capacity	Up to 8 TBcapacity for each disk
USB Interface	2 × USB 2.0
Alarm In/Out	N/A (4/1 is optional)
General	
Power Supply	12 VDC, 1.5 A
Consumption	≤ 10 W (without HDD)
Working Temperature	-10 °C to 55 °C(14 °F to 131 °F)
Working Humidity	10% to 90%

Dimension (W × D × H)	320 × 240 × 48 mm (12.4" × 9.4" × 1.9")
Weight	≤ 1 kg (without HDD,2.2 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015,EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az