

# DS-7608NI-K2/8

DS-7608NI-K2/8 POE 4K NETWORK VIDEO RECORDER HIKVISION



## Specifications

Model	DS-7608NI-K2/8
Brand	Hikvision
Növ	NVR
Kanal say?	8 kanal
PoE d?st?yi	PoE
Meqapixel	8 MP
Max HDD say?	2 HDD
Max HDD h?cmi	8 TB

## KEY FEATURES

Motion Detection 2.0	
Human/Vehicle Analysis	4-ch
Video and Audio	
IP Video Input	8-ch
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60Hz
VGA Output	1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
Video OutputMode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	8-ch
Decoding Capability	1-ch@8 MP (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps)
Stream Type	Video, Video &Audio
Audio Compression	G.711ulaw,G.711alaw,G.722,G.726,AAC,MP2L2
Network	
Network Interface	1 RJ-45 10/100 Mbpsself-adaptive Ethernet interface TCP/IP, DHCP, IPv4,IPv6, DNS, DDNS, NTP, RTSP,
Network Protocol	SADP, SMTP,SNMP, NFS, iSCSI,ISUP, UPnP™, HTTP,HTTPS
Remote Connection	32
PoE	
Interface	8, RJ-45 10/100 Mbpsself-adaptive Ethernet interface
Power	≤ 80 W
Standard	IEEE 802.3 af/at
Wireless Parameter	
SIM/UIM CardSlot	1 micro SIM cardslot, on rear panel 1 4G interface, antenna module cablelength: 3 m
SMA Antenna Interface	1 ANT interface forGPS antenna (GPSantenna is optional)

---

	<b>GSM/EDGE: 850/900/1800MHz WCDMA:B1/B5/B8</b>
	<b>LTE-FDD: B1/B3/B5/B7/B8/B20/B28</b>
<b>Wireless Standard</b>	<b>LTE-TDD: B38/B40/B41</b>
<b>Auxiliary Interface</b>	
<b>SATA</b>	<b>2 SATA interfaces</b>
<b>Capacity</b>	<b>Up to 8 TB capacity for each disk</b>
<b>USB Interface</b>	<b>Front panel: 1 × USB 2.0;Rear panel: 1 × USB2.0</b>
<b>General</b>	
<b>Power Supply</b>	<b>48 VDC, 2.5 A</b>
<b>Consumption</b>	<b>≤ 15 W (without HDD and PoE off)</b>
<b>Working Temperature</b>	<b>-10 °C to 55 °C (14 °F to 131 °F)</b>
<b>Working Humidity</b>	<b>10% to 90%</b>
<b>Dimension (W × D × H)</b>	<b>385 × 315 × 52 mm (15.2" × 12.4" × 2.0")</b>
<b>Weight</b>	<b>≤ 3 kg (without HDD, 6.6 lb.)</b>