

DS-7608NI-K2/8

DS-7608NI-K2/8 POE 4K NETWORK VIDEO RECORDER HIKVISION



Model	DS-7608NI-K2/8
Brend	Hikvision
Növ	NVR
Kanal sayı	8 kanal
PoE dəstəyi	PoE
Məqəpixel	8 MP
Max HDD sayı	2 HDD
Max HDD həcmi	8 TB

Specification

Motion Detection 2.0	
Human/Vehicle Analysis	4-ch
Video and Audio	
IP Video Input	8-ch
Incoming Bandwidth	80 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30Hz, 2K (2560 x 1440)/60 Hz, 1920 x 1080/60 Hz, 1600 x 1200/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60Hz
VGA Output	1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Decoding	
Decoding Format	H.265+/H.265/H.264+/H.264
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	8-ch
Decoding Capability	1-ch@8 MP (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps)

Stream Type	Video, Video &Audio
Audio Compression	G.711ulaw,G.711alaw,G.722,G.726,AAC,MP2L2
Network	
Network Interface	1 RJ-45 10/100 Mbpsself-adaptive Ethernet interface
Network Protocol	TCP/IP, DHCP, IPv4,IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP,SNMP, NFS, iSCSI,ISUP, UPnP™, HTTP,HTTPS
Remote Connection	32
PoE	
Interface	8, RJ-45 10/100 Mbpsself-adaptive Ethernet interface
Power	≤ 80 W
Standard	IEEE 802.3 af/at
Wireless Parameter	
SIM/UIM CardSlot	1 micro SIM cardslot, on rear panel
SMA Antenna Interface	1 4G interface, antenna module cablelength: 3 m 1 ANT interface forGPS antenna (GPSantenna is optional)

Wireless Standard	GSM/EDGE: 850/900/1800MHz WCDMA:B1/B5/B8 LTE-FDD: B1/B3/B5/B7/B8/B20/B28 LTE-TDD: B38/B40/B41
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 8 TB capacity for each disk
USB Interface	Front panel: 1 × USB 2.0;Rear panel: 1 × USB2.0
General	
Power Supply	48 VDC, 2.5 A
Consumption	≤ 15 W (without HDD and PoE off)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Dimension (W × D × H)	385 × 315 × 52 mm (15.2" × 12.4" × 2.0")
Weight	≤ 3 kg (without HDD, 6.6 lb.)