

HIKVISION

DS-7616NI-K2/16 POE

Kod: 00-00004038 · Videoregistrator



Hikvision DS-7616NI-K2/16 PoE NVR, 16 kanal video giriş və PoE portları ilə IP kameraları birbaşa qoşmağa imkan verir. Yüksək keyfiyyətli qeyd, uzaqdan idarəetmə və etibarlı şəbəkə nəzarəti üçün ideal həll.

Qiymət, stok və sifariş üçün: [Məhsul səhifəsinə keçin →](#)<https://eurotechnology.az/product/hikvision/ds-7616ni-k216-poe>

Texniki göstəricilər

**NVR**

Növ

**16 kanal**

Kanal sayı

**PoE**

PoE dəstəyi

**12 MP**

Məqapixel

**2 HDD**

Max HDD sayı

**16 TB**

Max HDD həcmi

Ətraflı məlumat

Category	Specification
Video Parameter	
Decoding Capability	8 × 1080P
IP Video Input	16-ch
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	160 Mbps
HDMI Output	4K (3840 × 2160)/30 Hz, 2K (2560 × 1440)/60 Hz, 1080p/60 Hz, 1600 × 1200/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz
VGA Output	1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz
Video Output Mode	HDMI/VGA independent output
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using audio input)
Decoding Format	H.265/H.265+/H.264/H.264+
Recording Resolution	12 MP / 8 MP / 6 MP / 5 MP / 4 MP / 3 MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Synchronous Playback	16-ch
Decoding Capability (Playback)	Smooth Playback (HC) ON: 1-ch@12 MP / 2-ch@8 MP / 4-ch@4 MP / 9-ch@1080p Smooth Playback (HC) OFF: 1-ch@12 MP / 2-ch@8 MP / 5-ch@4 MP / 10-ch@1080p
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726
Network	
Remote Connection	128-ch
Network Protocols	TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
Network Interface	1 × RJ-45 10/100/1000 Mbps self-adaptive Ethernet

Category	Specification
PoE Interface	16 × RJ-45 10/100 Mbps self-adaptive Ethernet
Storage	
Auxiliary Interface	2 × SATA interfaces, up to 16 TB per HDD
USB Interface	Front: 1 × USB 2.0, Rear: 1 × USB 2.0
Alarm	4 inputs / 1 output
General	
Power Supply	100 – 240 VAC, 50 – 60 Hz
Power Consumption	≤ 15 W (without HDD, PoE off)
PoE Power Budget	≤ 200 W, IEEE 802.3 af/at
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10 – 90 %
Dimensions (W × D × H)	385 × 315 × 52 mm (15.2" × 12.4" × 2.0")
Weight	≤ 3 kg (without HDD, 6.6 lb.)
Certification	FCC Part 15 Subpart B, ANSI C63.4-2014; CE EN 55032:2015, EN 61000-3-2

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az