

DS-7616NI-Q2/16

DS-7616NI-Q2/16 POE NETWORK DIGITAL VIDEO RECORDER HIKVISION

Model	DS-7616NI-Q2/16
Brend	Hikvision
Növ	NVR
Kanal sayı	16 kanal
PoE dəstəyi	PoE
Məqəpixel	8 MP
Max HDD sayı	2 HDD
Max HDD həcmi	8 TB



Specification

Motion Detection 2.0	
Human/Vehicle Analysis	4-ch
Video and Audio	
IP Video Input	16-ch
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	80 Mbps
HDMI Output	1-ch, 4K (4096 x 2160)/30 Hz, 4K (3840 x 2160)/30 Hz, 2K (2560 x 1440)/60Hz, 1920 x 1080/60 Hz, 1600 x 1200/60Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
VGA Output	1-ch, 1920 x 1080/60 Hz, 1280 x 1024/60 Hz, 1280 x 720/60 Hz
Video Output Mode	HDMI/VGA simultaneous output
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0Vp-p, 1 k Ω)
Decoding	
Decoding Format	H.265+, H.265, H.264+, H.264
Recording Resolution	8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA /720p/VGA/4CIF/DCIF/ 2CIF/CIF/QCIF
Synchronous playback	16-ch
Decoding Capability	1-ch@8 MP (30 fps)/3-ch@4 MP (30 fps)/6-ch@1080p (30 fps) *: The length or width of camera resolution (each track) cannot exceed 4096 pixels.
Stream Type	Video, Video & Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726

Network	
Remote Connection	32
API	ONVIF (profile S/G);SDK; ISAPI
Network Protocol	TCP/IP, DHCP, IPv4,IPv6, DNS, DDNS,NTP, RTSP, SADP,SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP,HTTPS
Network Interface	1, RJ-45 10/100/1000 Mbpsself-adaptive Ethernet interface
PoE	
Interface	16, RJ-45 10/100 Mbpsself-adaptive Ethernet interface
Power	≤ 150 W
Standard	IEEE 802.3 af/at
Auxiliary Interface	
SATA	2 SATA interfaces
Capacity	Up to 8 TB capacity for each disk
Alarm In/Out	N/A (4/1 is optional)
USB Interface	2 × USB 2.0

General	
Power Supply	100 to 240 VAC,50 to 60 Hz
Consumption	≤ 15 W (without HDD and PoE off)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10% to 90%
Chassis	1U chassis
Dimension (W × D × H)	385 × 315 × 52 mm (15.2"× 12.4" × 2.0")
Weight	≤ 2.6 kg (without HDD,5.7 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015,EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017