

DS-7616NI-Q2/16P POE

Hikvision DS-7616NI-Q2/16P 16-kanallı PoE NVR, asan quraşdırma və PoE dəstəyi ilə tam video nəzarət təmin edir. Yüksək keyfiyyətli 1080p video qeydiyyatı, uzaqdan idarəetmə və etibarlı performans ilə kiçik və orta obyektlər üçün ideal həll.



Specifications

Model	DS-7616NI-Q2/16P POE
Brand	Hikvision
Növ	NVR
Kanal say?	16 kanal
PoE d?st?yi	PoE
Meqapixel	8 MP
Max HDD say?	2 HDD
Max HDD h?cmi	8 TB

KEY FEATURES

Category	Specification
Motion Detection 2.0	Human/Vehicle Analysis: 4-ch
Video Input	IP: 16-ch
Video Output	HDMI: 1-ch, 4K (4096×2160/3840×2160)@30Hz, 2K (2560×1440)/60Hz, 1080p/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz VGA: 1-ch, 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz Output mode: HDMI/VGA simultaneous
Bandwidth	Incoming: 160 MbpsOutgoing: 80 Mbps
Audio	Output: 1-ch RCA (Linear, 1 KΩ) Two-way audio: 1-ch RCA (2.0 Vp-p, 1 KΩ)
Decoding	Formats: H.265+, H.265, H.264+, H.264 Capability: 1-ch @ 8 MP (30 fps), 5-ch @ 1080p (30 fps) Synchronous playback: 16-ch
Recording Resolution	8 MP / 6 MP / 5 MP / 4 MP / 3 MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Network	Protocols: TCP/IP, DHCP, Hik-Connect, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS Interface: 1 × RJ45 10/100/1000 Mbps
PoE	16 × RJ45 10/100 Mbps
Power	≤ 150 WSupply: 100-240V~, 50/60Hz, 3.2A maxStandard: IEEE 802.3 af/at
RAID	None
Auxiliary Interface	SATA: 2 × up to 8TB per disk USB: 2 × USB 2.0
General	Consumption: ≤ 15 W Temperature: -10 to +55 °C Humidity: 10–90 % Chassis: 1U Dimension (W×D×H): 385 × 315 × 52 mm (15.2"×12.4"×2.0") Weight: ≤ 2.6 kg (5.7 lb)