eurotech
Taste of technology

TEXNIKI SƏNƏD

10.11.2026

HIKVISION

DS-7632NI-K2

Kod: 00-00000455 · Videoregistrator



Hikvision DS-7632NI-K2 32-kanallı Network Video Recorder, böyük obyektlər üçün ideal təhlükəsizlik həllidir. Yüksək keyfiyyətli video qeydiyyatı, uzaqdan izləmə və etibarlı performans təmin edir, quraşdırması sadə və istifadəsi rahatdır.

Texniki göstəricilər

NVR	Növ
32 kanal	Kanal sayı
12 MP	Meqapixel
2 HDD	Max HDD sayı
16 TB	Max HDD həcmi

Ətraflı məlumat

Category	Specification
IP Video Input	32 channels
Bandwidth	Incoming: 256 Mbps Outgoing: 160 Mbps
Video Output	HDMI: 4K (3840×2160)/30Hz, 2K (2560×1440)/60Hz, 1080p/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz VGA: 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz Output Mode: HDMI/VGA independent
Audio	Input: 1-ch RCA (2.0 Vp-p, 1 KΩ) Output: 1-ch RCA (Linear, 1 KΩ) Two-Way Audio: 1-ch RCA (using audio input) Compression: G.711u / G.711a / G.722 / G.726
Decoding	Format: H.265 / H.265+ / H.264 / H.264+ Capability (HC ON): 1-ch@12MP, 2-ch@8MP, 4-ch@4MP, 9-ch@1080p Capability (HC OFF): 1-ch@12MP, 2-ch@8MP, 5-ch@4MP, 10-ch@1080p Synchronous Playback: 16-ch
Recording Resolution	12 MP / 8 MP / 6 MP / 5 MP / 4 MP / 3 MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Stream Type	Video, Video & Audio
Network	Remote Connection: 128-ch Protocol: TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS Interface: 1 × RJ45 10/100/1000 Mbps
Auxiliary Interface	SATA: 2 × up to 16TB per HDD USB: Front 1 × USB 2.0, Rear 1 × USB 2.0
Alarm	Input/Output: 4 / 1

Category	Specification
Power	Supply: 12 VDC, 3.33 A Consumption: ≤ 15 W (without HDD)
Operating Conditions	Temp: -10°C to 55°CHumidity: 10–90%
Dimensions & Weight	385 × 315 × 52 mm (15.2" × 12.4" × 2.0")Weight: ≤ 1 kg (without HDD)
Certification	FCC, CE

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az