

DS-7632NI-K2

Hikvision DS-7632NI-K2 32-kanallı Network Video Recorder, böyük obyektlər üçün ideal təhlükəsizlik həllidir. Yüksək keyfiyyətli video qeydiyyatı, uzaqdan izləmə və etibarlı performans təmin edir, quraşdırması sadə və istifadəsi rahatdır.



Specifications

Model	DS-7632NI-K2
Brand	Hikvision
Növ	NVR
Kanal say?	32 kanal
Meqapixel	12 MP
Max HDD say?	2 HDD
Max HDD h?cmi	16 TB

KEY FEATURES

Category	Specification
IP Video Input	32 channels
Bandwidth	Incoming: 256 Mbps Outgoing: 160 Mbps
Video Output	HDMI: 4K (3840×2160)/30Hz, 2K (2560×1440)/60Hz, 1080p/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz VGA: 1080p/60Hz, 1280×1024/60Hz, 1280×720/60Hz Output Mode: HDMI/VGA independent
Audio	Input: 1-ch RCA (2.0 Vp-p, 1 KΩ) Output: 1-ch RCA (Linear, 1 KΩ) Two-Way Audio: 1-ch RCA (using audio input) Compression: G.711u / G.711a / G.722 / G.726
Decoding	Format: H.265 / H.265+ / H.264 / H.264+ Capability (HC ON): 1-ch@12MP, 2-ch@8MP, 4-ch@4MP, 9-ch@1080p Capability (HC OFF): 1-ch@12MP, 2-ch@8MP, 5-ch@4MP, 10-ch@1080p Synchronous Playback: 16-ch
Recording Resolution	12 MP / 8 MP / 6 MP / 5 MP / 4 MP / 3 MP / 1080p / UXGA / 720p / VGA / 4CIF / DCIF / 2CIF / CIF / QCIF
Stream Type	Video, Video & Audio
Network	Remote Connection: 128-ch Protocol: TCP/IP, DHCP, IPv4/IPv6, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS Interface: 1 × RJ45 10/100/1000 Mbps
Auxiliary Interface	SATA: 2 × up to 16TB per HDD USB: Front 1 × USB 2.0, Rear 1 × USB 2.0
Alarm	Input/Output: 4 / 1
Power	Supply: 12 VDC, 3.33 A Consumption: ≤ 15 W (without HDD)
Operating Conditions	Temp: -10°C to 55°CHumidity: 10–90%
Dimensions & Weight	385 × 315 × 52 mm (15.2" × 12.4" × 2.0")Weight: ≤ 1 kg (without HDD)
Certification	FCC, CE