

DS-7716NXI-K4

DS-7716NXI-K4 16-ch 1.5U K Series AcuSense 4K NVR HIKVISION



Model	DS-7716NXI-K4
Brend	Hikvision
Növ	NVR
Kanal sayı	16 kanal
Max HDD sayı	4 HDD
Meqapixel	12 MP
Max HDD həcmi	10 TB

Specification

Intelligent Analytics	
AI by Device	Facial recognition, perimeter protection, motiondetection 2.0
AI by Camera	Facial recognition, perimeter protection, throwing objectsfrom building, motion detection2.0, ANPR,VCA
Facial Recognition	
Facial Detection and Analytics	Face picture comparison, human facecapture, face picture search
Face Picture Library	Up to 16 facepicture libraries, withup to 20,000 face pictures in total (each picture ≤ 4 MB, total capacity ≤ 1 GB)
Facial Detection and Analytics Performance	1-ch, 8 MP
Face Picture Comparison	4-ch
Motion Detection 2.0	
By Device	All channels, up to 4 MP (when enhanced SVC mode is enabled, up to 8 MP) video analysis for human and vehicle recognition to reduce falsealarm
By Camera	All channels
Perimeter Protection	

By Device	2-ch, 4 MP (HD networkcamera, H.264/H.265) videoanalysis for humanand vehicle recognition to reduce falsealarm
By Camera	All channels
Video and Audio	
IP Video Input	16-ch
Incoming Bandwidth	160 Mbps
Outgoing Bandwidth	160 Mbps
HDMI Output	1-ch, 4K (3840× 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
Video OutputMode	HDMI/VGA independent output
CVBS Output	N/A
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, usingthe audio input)
Decoding	
Decoding Format	H.265/H.265+/H.264+/H.264
Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	16-ch

Decoding Capability	AI on: 1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p (30 fps) AI off: 2-ch@12 MP (30 fps)/3-ch@8 MP (30 fps)/6-ch@4 MP (30 fps)/12-ch@1080p (30 fps)
Stream Type	Video, Video &Audio
Audio Compression	G.711ulaw/G.711alaw/G.722/G.726/AAC
Network	
Remote Connection	128
API	ONVIF (profile S/G);SDK; ISAPI
Compatible Browser	IE11, Chrome V57,Firefox V52, SafariV12, Edge V89,or above version
Network Protocol	TCP/IP, DHCP,IPv4, IPv6, DNS, DDNS, NTP, RTSP, SADP,SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP,HTTPS
Network Interface	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
Auxiliary Interface	
SATA	4 SATA interfaces
Capacity	Up to 10 TBcapacity for eachHDD
Serial Interface	2 RS-485 (half-duplex), 1 RS-232
Alarm In/Out	16/4 (16/9 is optional)
USB Interface	Front panel: 2 × USB 2.0;Rear panel: 1 × USB3.0
Ctrl 12V	N/A (optional to support)
DC 12V	N/A (optional to support)
General	

GUI Language	English, Russian, Bulgarian, Hungarian, Greek, German, Italian, Czech, Slovak, French, Polish, Dutch, Portuguese, Spanish, Romanian, Turkish, Japanese, Danish, Swedish Language, Norwegian, Finnish, Korean, Traditional Chinese, Thai, Estonian, Vietnamese, Croatian, Slovenian, Serbian, Latvian, Lithuanian, Uzbek, Kazakh, Arabic, Ukrainian, Kyrgyz, Brazilian Portuguese, Indonesian
Power Supply	100 to 240 VAC, 50 to 60Hz
Consumption	≤ 20 W (without HDD)
Working Temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working Humidity	10 to 90 %
Dimension (W × D × H)	445 × 400 × 75 mm (17.5"× 15.7" × 3.0")
Weight	≤ 5 kg (without HDD, 11 lb.)
Certification	
FCC	Part 15 Subpart B, ANSI C63.4-2014
CE	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017