

DS-7716NXI-K4

DS-7716NXI-K4 16-ch 1.5U K Series AcuSense 4K NVR HIKVISION



Specifications

Model	DS-7716NXI-K4
Brand	Hikvision
Növ	NVR
Kanal say?	16 kanal
Max HDD say?	4 HDD
Meqapixel	12 MP
Max HDD h?cmi	10 TB

KEY FEATURES**Intelligent Analytics****AI by Device** **Facial recognition, perimeter protection, motiondetection 2.0****Facial recognition, perimeter protection,****AI by Camera** **throwing objectsfrom building, motion**
detection2.0, ANPR,VCA**Facial Recognition****Facial Detection and Analytics** **Face picture comparison, human facecapture,****face picture search****Up to 16 facepicture libraries, withup to 20,000 face pictures in total (each picture ≤ 4****Face Picture Library** **MB, total capacity ≤ 1 GB)****Facial Detection and Analytics****Performance** **1-ch, 8 MP****Face Picture Comparison** **4-ch****Motion Detection 2.0****All channels, up to 4 MP (when enhanced SVC****By Device** **mode is enabled, up to 8 MP) video****analysis for human and vehicle recognition to****reduce falsealarm****By Camera** **All channels****Perimeter Protection****2-ch, 4 MP (HD networkcamera, H.264/H.265)****By Device** **videoanalysis for humanand vehicle****recognition to reduce falsealarm****By Camera** **All channels****Video and Audio****IP Video Input** **16-ch****Incoming Bandwidth** **160 Mbps****Outgoing Bandwidth** **160 Mbps**

	1-ch, 4K (3840× 2160)/30Hz, 2K (2560 × 1440)/60Hz,
HDMI Output	1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280× 1024/60Hz, 1280× 720/60Hz, 1024× 768/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz
Video OutputMode	HDMI/VGA independent output
CVBS Output	N/A
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Two-Way Audio	1-ch, RCA (2.0 Vp-p, 1 KΩ, using the audio input)
Decoding	
Decoding Format	H.265/H.265+/H.264+/H.264
Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous playback	16-ch

AI on: 1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p (30 fps)

AI off: 2-ch@12 MP (30 fps)/3-ch@8 MP (30 fps)/6-ch@4 MP (30 fps)/12-ch@1080p (30

Decoding Capability fps)

Stream Type Video, Video & Audio

Audio Compression G.711ulaw/G.711alaw/G.722/G.726/AAC

Network

Remote Connection 128

API ONVIF (profile S/G);SDK; ISAPI

Compatible Browser IE11, Chrome V57,Firefox V52, SafariV12,

Edge V89, or above version

TCP/IP, DHCP, IPv4, IPv6, DNS, DDNS, NTP,

Network Protocol RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP,

UPnP™, HTTP, HTTPS

Network Interface 2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces

Auxiliary Interface

SATA 4 SATA interfaces

Capacity Up to 10 TB capacity for each HDD

Serial Interface 2 RS-485 (half-duplex), 1 RS-232

Alarm In/Out 16/4 (16/9 is optional)

USB Interface Front panel: 2 × USB 2.0; Rear panel: 1 × USB3.0

Ctrl 12V N/A (optional to support)

DC 12V N/A (optional to support)

General