

# DS-7732NI-K4

## DS-7732NI-K4 NETWORK DIGITAL VIDEO RECORDER HIKVISION



Model	DS-7732NI-K4
Brend	Hikvision
Növ	NVR
Kanal sayı	32 kanal
Meqapixel	12 MP
Max HDD sayı	4 HDD
Max HDD həcmi	10 TB

### Specification

Video and Audio	
IP Video Input	32-ch
Incoming Bandwidth	256 Mbps
Outgoing Bandwidth	160 Mbps
HDMI Output	1-ch, 4K (3840 × 2160)/30Hz, 2K (2560 × 1440)/60Hz, 1920 × 1080/60Hz, 1600 × 1200/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
VGA Output	1-ch, 1920 × 1080/60Hz, 1280 × 1024/60Hz, 1280 × 720/60Hz, 1024 × 768/60Hz
Video OutputMode	HDMI/VGA independent output
CVBS Output	N/A
Audio Input	1-ch, RCA (2.0 Vp-p, 1 KΩ)
Audio Output	1-ch, RCA (Linear, 1 KΩ)
Decoding	
Decoding Format	H.265/H.265+/H.264+/H.264
Recording Resolution	12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/UXGA/ 720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF
Synchronous Playback	16-ch
Decoding Capability	1-ch@12 MP (30 fps)/2-ch@8 MP (30 fps)/4-ch@4 MP (30 fps)/8-ch@1080p(30 fps)

<b>Stream Type</b>	Video, Video& Audio
<b>Audio Compression</b>	G.711ulaw/G.711alaw/G.722/G.726/ACC/MP2L2
<b>Network</b>	
<b>Remote Connection</b>	128-ch
<b>Network Protocol</b>	TCP/IP, DHCP, IPv4, Hik-Connect, DNS, DDNS, NTP, RTSP, SADP, SMTP, SNMP, NFS, iSCSI, ISUP, UPnP™, HTTP, HTTPS
<b>Network Interface</b>	2 RJ-45 10/100/1000 Mbps self-adaptive Ethernet interfaces
<b>Auxiliary Interface</b>	
<b>SATA</b>	4 SATA interfaces
<b>Capacity</b>	Up to 10 TB capacity for each HDD
<b>Serial Interface</b>	2 RS-485 (half-duplex), 1 RS-232
<b>USB Interface</b>	Front panel: 2 × USB 2.0; Rear panel: 1 × USB 3.0
<b>Alarm In/Out</b>	16/4 (16/9 is optional)
<b>General</b>	
<b>Power Supply</b>	100 to 240 VAC, 50 to 60Hz
<b>Consumption</b>	≤ 20 W (without HDD)
<b>Working Temperature</b>	-10 °C to 55 °C (14 °F to 131 °F)
<b>Working Humidity</b>	10 to 90 %
<b>Dimension (W × D × H)</b>	445 × 400 × 71 mm ( 17.5" × 15.7" × 2.8")

<b>Weight</b>	≤ 5 kg (without HDD, 11 lb.)
<b>Certification</b>	
<b>FCC</b>	Part 15 Subpart B, ANSI C63.4-2014
<b>CE</b>	EN 55032: 2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4, EN 55035: 2017