

# DS-8664NI-I8

DS-8664NI-I8 NETWORK DIGITAL VIDEO RECORDER HIKVISION



## Specifications

Model	DS-8664NI-I8
Brand	Hikvision
Növ	NVR
Kanal say?	64 kanal
Meqapixel	12 MP
Max HDD say?	8 HDD
Max HDD h?cmi	10 TB

## KEY FEATURES

### Video and audio

<b>IP video input</b>	<b>64 channels</b> <b>Resolution up to 12 MP</b> <b>32 MP/24 MP/ 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/</b> <b>UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF</b> *: resolution 32 MP and 24 MP are only available for channel 1 when Ultra HD resolution mode is enabled.
<b>Input Bandwidth</b>	<b>320 Mbit/s</b>
<b>Output Bandwidth</b>	<b>256 Mbit/s</b>
<b>Input Bandwidth (RAID Mode)</b>	<b>200 Mb/s</b>
<b>Output Bandwidth (RAID Mode)</b>	<b>200 Mb/s</b>
<b>1 HDMI output</b>	<b>4K (3840×2160)/60Hz, 4K (3840×2160)/30Hz, 1920×1080/60Hz, 1600×1200/60Hz, 1280×1024/60Hz, 1280×720/60Hz, 10 24× 768/60 Hz</b>
<b>2 HDMI output</b>	<b>1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz</b>
<b>1 VGA output</b>	<b>1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz</b>
<b>2 VGA output</b>	<b>1920 × 1080p/60 Hz, 1280 × 1024/60 Hz, 1280 × 720/60 Hz, 1024 × 768/60 Hz</b>
<b>Video output</b>	<b>1 HDMI and 1 VGA provide simultaneous video output and is used as the main output;</b> <b>2 HDMI and 2 VGA provide simultaneous video output and can be used as auxiliary output;</b>
<b>CVBS output (optional)</b>	<b>1 channel, BNC (1.0 V pp, 75 Ohm), resolution: PAL: 704 × 576, NTSC: 704 × 480</b>
<b>Audio output</b>	<b>2 channels, RCA (linear, 1 kOhm)</b>
<b>Two-way audio</b>	<b>1 channel, RCA (2.0 V pp, 1 kOhm, when using audio input)</b>

### Decoding

<b>Decoding Format</b>	<b>H.265+/H.265/H.264+/H.264/MPEG4</b>
<b>Recording permission</b>	<b>32 MP/24 MP/12 MP/8 MP/6 MP/5 MP/4 MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF</b> <b>32 MP/24 MP/12 MP/8 MP/6MP/5MP/4MP/3MP/1080p/UXGA/720p/VGA/4CIF/DCIF/2CIF/CIF/QCIF</b> *: 32MP and 24MP resolution is only available for channel 1 when Ultra resolution mode is enabled HD.
<b>Synchronized playback</b>	<b>16 channels</b>
<b>Playback options</b>	<b>1 channel, @ 32 MP (30 fps)/2 channels, @ 12 MP (20 fps)/4 channels, @ 8 MP (25 fps)/8 channels @ 4 MP (30 fps) /16 channels @ 1080p (30 fps)</b>
<b>Dual stream recording</b>	<b>Supported</b>
<b>Stream type</b>	<b>Video, video and audio</b>
<b>Audio compression</b>	<b>G.711ulaw/G.711alaw/G.722/G.726</b>

### Net

<b>Remote connections</b>	<b>128</b>
<b>Protocols</b>	<b>TCP/IP, DHCP, HIK Cloud P2P, DNS, DDNS, NTP, SADP, SMTP, NFS, iSCSI, UPnP™, HTTPS</b>

### RAID

---

**RAID type** RAID0, RAID1, RAID5, RAID6 and RAID10 (minimum 4 TB for each HDD)

## Auxiliary Interfaces

<b>Serial interface</b>	RS-232; RS-485; keyboard
<b>SATA</b>	8 SATA interfaces
<b>eSATA</b>	1 eSATA interface
<b>Capacity</b>	Up to 10 TB each drive
<b>Alarm input/output</b>	16/4
<b>USB</b>	Front panel: 2 × USB 2.0; rear panel: 1 × USB 3.0

## Basics

<b>Nutrition</b>	AC 100 to 240 V, 50 to 60 Hz
<b>Power consumption (without HDD)</b>	≤30W
<b>Working temperature</b>	-10 to +55 °C
<b>Operating humidity</b>	From 10 to 90%
<b>Dimensions</b>	445 × 470 × 94 mm
<b>Weight (without storage)</b>	≤ 8 kg

## Certificates

<b>FCC</b>	Part 15 Subpart B, ANSI C63.4-2014
<b>C.E.</b>	EN 55032:2015, EN 61000-3-2, EN 61000-3-3, EN 50130-4