

# DS-E04HGHI-B

DS-E04HGHI-B 4-CH 1080P LITE 1U H.265 BUILT-IN 330 GB eSSD DVR HIKVISION



## Specifications

Model	DS-E04HGHI-B
Brand	Hikvision
Növ	XVR
Kanal say?	4 kanal
Meqapixel	2 MP





## KEY FEATURES

### Motion Detection 2.0

Deep learning-based motiondetection 2.0 is enabled by default for all analog channels, it can classify human and vehicle, and extremely reduce false alarms caused by objects like leavesand lights;

Human/Vehicle Analysis Quick search by object or event typeis supported;

### Recording

Video Compression H.265 Pro/H.265

Encoding Resolution 1080p Lite/720p/720p Lite/WD1/4CIF/CIF/QVGA

Main stream:

1080p Lite/720p/720p Lite/WD1/4CIF@25 fps (P)/30 fps (N) Note:

1080p Lite/720p is 15 fpsby default Sub-stream:

4CIF@15 fps;CIF/QVGA@25 fps (P)/30fps (N)

### Frame Rate

According to the actual scene,scene-adaptive bitrate control technology would

Video Bitrate automatically allocates appropriate bitrate to ensure the stability of recording period.

Video, Video& Audio

Note: In order to protect privacy, the device will only record video (without audio) by default. If you want to record audio, you shall manually enable audio recording. For operation details, refer to theuser manual.

### Stream Type

Audio Compression G.711u

Audio Bitrate 64 Kbps

### Video and Audio

1-ch

Up to 1080presolution

IP Video Input Support H.265+/H.265 IP cameras

4-ch

Analog VideInput BNC interface (1.0 Vp-p,75 Ω), supporting coaxitron connection

HDTVl Input 1080p25, 1080p30, 720p25,720p30

AHD Input 1080p25, 1080p30, 720p25, 720p30

HDCVl Input 1080p25, 1080p30, 720p25,720p30

CVBS Input Support

HDMI Output 1-ch, 1920 × 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz

VGA Output 1-ch, 1920× 1080/60Hz, 1280× 1024/60Hz, 1280 ×720/60Hz

Video OutputMode HDMI/VGA simultaneous output

Audio Input 4-ch via coaxial cable

Audio Output 1-ch via HDMI

Synchronous playback 4-ch