

# DS-KH6320-WTE1 WHITE

DS-KH6320-WTE1 AG IP VIDEO DOMOFON HIKVISION



## Specifications

Model	DS-KH6320-WTE1 White
Brand	Hikvision
Ba?lant? tipi	IP
Cihaz	Monitor
WIFI	WIFI
Yadda?	SD Card
Material	Plastik

## KEY FEATURES

### System parameters

<b>Operation system</b>	<b>Linux</b>
<b>ROM</b>	<b>32 MB</b>
<b>RAM</b>	<b>128 MB</b>
<b>Processor</b>	<b>Embedded highperformance processor</b>

### Display parameters

<b>Screen size</b>	<b>7-inch</b>
<b>Operation method</b>	<b>Capacitive touch screen</b>
<b>Type</b>	<b>Colorful TFT</b>
<b>Resolution</b>	<b>1024 × 600</b>

### Video parameters

<b>Lens</b>	/
<b>Resolution</b>	/
<b>FOV</b>	/
<b>Wide dynamic range(WDR)</b>	/
<b>Video compression standard</b>	/
<b>Focal length</b>	/

### Audio parameters

<b>Audio input</b>	<b>1 built-in omnidirectional microphone</b>
<b>Audio compression standard</b>	<b>G.711U/G.711A</b>
<b>Audio output</b>	<b>1 built-in loudspeaker</b>
<b>Audio compression bitrate</b>	<b>64 Kbps</b>
<b>Audio quality</b>	<b>Noise suppression and echo cancellation</b>
<b>Volume adjustment</b>	<b>Adjustable</b>

### Capacity

**TF card inser**

**ted: 200captured pictures, 200 alarmrecords**

<b>Message capacity</b>	<b>Without TF card: 2 MB RAM for picturestorage; The storage numberis decided by the picture size, 200 alarmrecords</b>
-------------------------	---

<b>Notice capacity</b>	<b>200</b>
------------------------	------------

<b>Linked indoorextensions</b>	<b>16</b>
--------------------------------	-----------

### capacity

<b>Linked doorphone capacity</b>	<b>17</b>
----------------------------------	-----------

<b>Linked networkcamera capacity</b>	<b>16</b>
--------------------------------------	-----------

### Network parameters

<b>Network protocol</b>	<b>TCP/IP, SIP,RTSP</b>
<b>Wi-Fi</b>	<b>2.4 GHz, IEEE802.11b, IEEE802.11g, IEEE802.11n</b>
<b>Bluetooth</b>	/
<b>3G/4G</b>	/
<b>Zigbee</b>	/

---

<b>Device interfaces</b>	
<b>Alarm input</b>	<b>8</b>
<b>Network interface</b>	<b>1 RJ-45 10/100 Mbps self-adaptive</b>
<b>TAMPER</b>	<b>/</b>
<b>RS-485</b>	<b>1 RS-485(Half duplex)</b>
<b>USB</b>	<b>/</b>
<b>TF card</b>	<b>Support TF card, up to 128 G</b>
<b>Alarm output</b>	<b>2</b>
<b>Lock control</b>	<b>2 relays, Max. 30 VDC 0.3 A</b>
<b>General</b>	
<b>Button</b>	<b>/</b>
<b>Installation</b>	<b>Surface mounting</b>
<b>Indicator</b>	<b>/</b>
<b>Weight</b>	<b>Net weight:355 g (0.8 lb)</b> <b>Gross weight: 683 g (1.5 lb)</b>
<b>Protective level</b>	<b>/</b>
<b>Working temperature</b>	<b>-10 °C to 55 °C (14 °F to 131 °F)</b>
<b>Working humidity</b>	<b>10% to 90% (no-condensing)</b>
<b>Dimension (W × H × D)</b>	<b>200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")</b>
<b>Battery</b>	<b>/</b>
<b>Application environment</b>	<b>Indoor</b>
<b>Power consumption</b>	<b>≤ 5 W</b>