

DS-KH6320-WTE1 White

DS-KH6320-WTE1 AG IP VIDEO DOMOFON HIKVISION

Model	DS-KH6320-WTE1 White
Brend	Hikvision
Bağlantı tipi	IP
Cihaz	Monitor
WIFI	WIFI
Yaddaş	SD Card
Material	Plastik



Specification

System parameters	
Operation system	Linux
ROM	32 MB
RAM	128 MB
Processor	Embedded highperformance processor
Display parameters	
Screen size	7-inch
Operation method	Capacitive touch screen
Type	Colorful TFT
Resolution	1024 × 600
Video parameters	
Lens	/
Resolution	/
FOV	/
Wide dynamic range(WDR)	/
Video compression standard	/
Focal length	/
Audio parameters	
Audio input	1 built-in omnidirectional microphone
Audio compression standard	G.711U/G.711A
Audio output	1 built-in loudspeaker
Audio compression bitrate	64 Kbps

Audio quality	Noise suppression and echo cancellation
Volume adjustment	Adjustable
Capacity	
Message capacity	TF card inser ted: 200captured pictures, 200 alarmrecords Without TF card: 2 MB RAM for picturestorage; The storage numberis decided by the picture size, 200 alarmrecords
Notice capacity	200
Linked indoorextensions capacity	16
Linked doorphone capacity	17
Linked networkcamera capacity	16
Network parameters	
Network protocol	TCP/IP, SIP,RTSP
Wi-Fi	2.4 GHz, IEEE802.11b, IEEE802.11g, IEEE802.11n
Bluetooth	/
3G/4G	/
Zigbee	/
Device interfaces	
Alarm input	8
Network interface	1 RJ-45 10/100 Mbpsself-adaptive
TAMPER	/
RS-485	1 RS-485(Half duplex)
USB	/
TF card	Support TF card, up to 128 G
Alarm output	2
Lock control	2 relays, Max. 30 VDC 0.3 A
General	
Button	/
Installation	Surface mounting
Indicator	/
Weight	Net weight:355 g (0.8 lb) Gross weight: 683 g (1.5 lb)
Protective level	/
Working temperature	-10 °C to 55 °C (14 °F to 131 °F)
Working humidity	10% to 90% (no-condensing)
Dimension (W × H × D)	200 mm × 140 mm × 15.1 mm (7.9" × 5.5" × 0.6")
Battery	/
Application environment	Indoor
Power consumption	≤ 5 W