

DS-KIS603-P(C)

Hikvision IP domofon DS-KIS603-P(C) kit; 7" TFT; 1024 × 600; WIFI; Plastik; PoE; Mikro SD; IC Card: 10000; Bucaq - 131°; IP653

Model	DS-KIS603-P(C)
Brend	Hikvision
Bağlantı tipi	IP
Cihaz	KİT
WIFI	WIFI
PoE	PoE
Yaddaş	SD Card
Material	Metal



Specification

Screen Options

Screen	7" color TFT LCD screen
Maximum screen resolution	1024x600
Working method	Touch screen, physical buttons

Audio

Audio input	Built-in omnidirectional microphone
Audio output	Built-in speaker
Audio compression	G.711 U, 64 Kbps
Audio quality	Noise and Echo Reduction

Network settings

Wired network	10 / 100 MB adaptive
Wireless network	Wi-Fi 802.11b/g/n
Network protocols	TCP/IP, SIP, RTSP
Network interface	1RJ45 10M/ 100M interface
Alarm inputs	8
TF card	Up to 32 GB, SD 2.0 or earlier
Power interface	2

Basics

Power supply	DC 12V, 1A PoE IEEE802.3 af
Power consumption	≤ 6 W
Working conditions	From -10 to +55 °C, humidity from 10 to 90%

Dimensions	200 × 140 × 15.1 mm
------------	---------------------

model

--

System parameters

operating system	Embedded Linux OS
Inner memory	32 MB
Memory	256 MB
CPU	Embedded MCU processor

Display options

Screen size	/
Control	/
Type	/
Permission	/

Video options

Lens	1
Permission	Main stream: 1920 × 1080p, 720p Sub stream: 704 × 576
Viewing angle	Horizontal: 131° Vertical: 78°
WDR	True WDR
Additional lighting	IR illumination
Video compression standard	H.264

Audio options

Audio compression standard	G.711 U
Audio input	Built-in omnidirectional microphone
Audio output	Built-in speaker
Audio bitrate	64 Kbps
Improved sound quality	Noise and echo reduction
Volume adjustment	Customizable

Capacity

Number of users	2000
Number of face images	/
Number of cards	10000

Network settings

Communication protocol	TCP/IP, RSTP
Wired network	Auto 10 / 100 M Ethernet
Wi-Fi standard	Supported
Bluetooth	Not supported
3G/4G standard	/

Device interfaces

Alarm input	4
Network interface	1
Tamper	1
Exit button	1
RS-485	0

USB	0
Wiegand	0
TF card	Reserved
Alarm output	0
Door lock indicator	1
Door contact input	1
Power interface	1

Basics

Button	1
Installation	Overhead installation
Indicator	2
Weight	265 g
Protection level	IP65
Working temperature	-40 to +53 °C
Operating humidity	From 10 to 95%
Dimensions	138 × 65 × 27 mm
Battery	/
terms of Use	Outside the premises
Power consumption	≈ 10W
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian