

# DS-KIS603-P(C)

Hikvision IP domofon DS-KIS603-P(C) kit; 7" TFT; 1024 × 600; WIFI; Plastik; PoE; Mikro SD; IC Card: 10000; Bucaq - 131°; IP653

Model	DS-KIS603-P(C)
Brend	Hikvision
Bağlantı tipi	IP
Cihaz	KİT
WIFI	WIFI
PoE	PoE
Yaddaş	SD Card
Material	Metal



## Specification

### Screen Options

Screen	7" color TFT LCD screen
Maximum screen resolution	1024×600
Working method	Touch screen, physical buttons

### Audio

Audio input	Built-in omnidirectional microphone
Audio output	Built-in speaker
Audio compression	G.711 U, 64 Kbps
Audio quality	Noise and Echo Reduction

### Network settings

Wired network	10 / 100 MB adaptive
Wireless network	Wi-Fi 802.11b/g/n
Network protocols	TCP/IP, SIP, RTSP
Network interface	1RJ45 10M/ 100M interface
Alarm inputs	8
TF card	Up to 32 GB, SD 2.0 or earlier
Power interface	2

### Basics

<b>Power supply</b>	DC 12V, 1A PoE IEEE802.3 af
<b>Power consumption</b>	≤ 6 W
<b>Working conditions</b>	From -10 to +55 °C, humidity from 10 to 90%
<b>Dimensions</b>	200 × 140 × 15.1 mm

model

System parameters

<b>operating system</b>	Embedded Linux OS
<b>Inner memory</b>	32 MB
<b>Memory</b>	256 MB
<b>CPU</b>	Embedded MCU processor

Display options

<b>Screen size</b>	/
<b>Control</b>	/
<b>Type</b>	/
<b>Permission</b>	/

Video options

<b>Lens</b>	1
<b>Permission</b>	Main stream: 1920 × 1080p, 720p Sub stream: 704 × 576
<b>Viewing angle</b>	Horizontal: 131° Vertical: 78°
<b>WDR</b>	True WDR
<b>Additional lighting</b>	IR illumination
<b>Video compression standard</b>	H.264

Audio options

<b>Audio compression standard</b>	G.711 U
<b>Audio input</b>	Built-in omnidirectional microphone
<b>Audio output</b>	Built-in speaker
<b>Audio bitrate</b>	64 Kbps
<b>Improved sound quality</b>	Noise and echo reduction
<b>Volume adjustment</b>	Customizable

Capacity

<b>Number of users</b>	2000
<b>Number of face images</b>	/
<b>Number of cards</b>	10000

Network settings

<b>Communication protocol</b>	TCP/IP, RSTP
<b>Wired network</b>	Auto 10 / 100 M Ethernet
<b>Wi-Fi standard</b>	Supported
<b>Bluetooth</b>	Not supported

3G/4G standard	/
----------------	---

## Device interfaces

Alarm input	4
Network interface	1
Tamper	1
Exit button	1
RS-485	0
USB	0
Wiegand	0
TF card	Reserved
Alarm output	0
Door lock indicator	1
Door contact input	1
Power interface	1

## Basics

Button	1
Installation	Overhead installation
Indicator	2
Weight	265 g
Protection level	IP65
Working temperature	-40 to +53 °C
Operating humidity	From 10 to 95%
Dimensions	138 × 65 × 27 mm
Battery	/
terms of Use	Outside the premises
Power consumption	⊕ 10W
Language	English, French, Portuguese (Brazil), Spanish, Russian, German, Italian, Polish, Arabic, Turkish, Vietnamese, Hungarian, Dutch, Romanian, Czech, Bulgarian, Ukrainian, Croatian, Serbian