

DS-T200L (3.6)

DS-T200L 3.6mm 2mp LED 20m ColorVu HD TVI Kamera HiWatch

Model	DS-T200L (3.6)
Brend	Hiwatch
Növ	Analoq
Meqapixel	2 MP
İşıqlandırma	LED
İşıqlandırma məsafəsi	20 m
Obyektiv	Sabit
Fokus	3.6
Qoruma	IP67
Material	Metal



Specification

Matrix	2 MP CMOS
Signal transmission standard	PAL/NTSC
Frame frequency	TVI: 1080p @ 25 fps or 30 fps CVI: 1080p @ 25 fps or 30 fps AHD: 1080p @ 25 fps or 30 fps CVBS: PAL/NTSC
Sensitivity	0.001 lux @ (F1.0, AGC on), 0 lux with white backlight
Electronic shutter speed	PAL: 1/25 to 1/50,000 s; NTSC: 1/30 to 1/50,000 s
Lens	Fixed lens 2.8mm, 3.6mm, 6mm
Viewing angle	2.8 mm, horizontal: 102°, vertical: 54°, diagonal: 121° 3.6 mm, horizontal: 80°, vertical: 43°, diagonal: 95° 6 mm, horizontal: 52°, vertical: 29°, diagonal: 61°
Lens mount	M12
Alarm light	Strobe (white light backlight), non-blinking light signal (white light backlight)
Day/night mode	Color
WDR	Digital WDR
Adjusting the viewing angle	Pan: 0 to 360°, Tilt: 0 to 180°, Rotation: 0 to 360°

Menu

White backlight	Auto/Off
Picture Mode	STD/HIGH-SAT/HIGHLIGHT
A.G.C.	Eat
Day/night mode	Color
White balance	Automatic/Manual
Exposure mode (automatic)	DWDR, BLC, HLC, Global.
Noise reduction	3D DNR/ 2D DNR
Language	English
Functions	Brightness, contrast, mirroring, defective pixel correction, sharpness, Anti-Banding function, intelligent backlight

Backlight mode	White backlight
----------------	-----------------

Interfaces

Video output	Switchable TVI/AHD/CVI/CVBS
--------------	-----------------------------

Basics

Working conditions	From -40 to +60 °C; Humidity: 90% or less (non-condensing)
Nutrition	DC 12V ± 25% It is recommended to use a separate power adapter for each camera.
Power consumption	Max. 2.4 W
Protection level	IP66
Material	Metal
White backlight range	Up to 20 m
Dimensions	162.7 × 70 × 70 mm (6.41 × 2.75 × 2.75)
Weight	Approx. 256.5 g