

DS-T206

DS-T206 2,8-12mm 2mp IR 30m HD TVI VF BULLET KAMERA HIWATCH

Model	DS-T206
Brend	Hiwatch
Növ	Analoq
Meqapixel	2 MP
Obyektiv	Varifokal
Fokus	2.7 - 13.5
İşıqlandırma	IR
İşıqlandırma məsafəsi	30 m
Qoruma	IP66
Material	Metal



Specification

Camera

Matrix	1/2.7 Progressive Scan CMOS
Number of effective pixels	1920x1080
Sensitivity	0.01lux @(F1.2, AGC on), 0lux with IR on
Electronic shutter speed	1/25s ~ 1/50,000s
Lens	Zoom lens 2.8 – 12mm @ F1.4
Lens mount	f14
Lens viewing angle	111.5° - 33.4°
Adjusting the installation angle	Pan: 0 - 360°, Tilt: 0 - 90°, Rotation: 0 - 360°
Synchronization	Internal
Permission	1080P @ 25fps
Day/Night mode	Mechanical IR cut filter with auto-switching
A.G.C.	High, medium, low, off.
Day/Night mode switching	Auto / color / black and white
Functions	Brightness, Sharpness, Mirroring, Smart-IR
Image enhancement	BLC, DNR, DWDR
Video output	1 HD-TVI/AHD/CVI/CVBS (switch button)

Basics

Nutrition	DC12V±15%
Communication interface	Coaxial cable HIKVISION-C (TVI output)

Power consumption	5W max.
Working conditions	-40°C – 60°C, humidity no more than 90%
Moisture protection	IP66
IR illumination range	up to 40m
Material	Metal/Plastic
Dimensions	256.4 × 83.3 × 78.2 mm
Weight	605gr.