HIWATCH

DS-T215(C)

Kod: 00-00000706 · Kamera



DS-T215(C) 5-75mm 2mp Optical Zoom 15X IR 100m HD Analog PTZ Kamera HiWatch

Texniki göstəricilər

Analoq Növ	**2 MP** Meqapixel
PTZ Obyektiv	**100m** İşıqlandırma məsafəsi
IP66 Qoruma	**Outdoor** İş mühiti
İR İşıqlandırma	**Metal** Material

Ətraflı məlumat

Camera

Matrix	1/2.8 Progressive Scan CMOS
Number of effective pixels	1920x1080
Sensitivity	Color: 0.005Lux@(F1.6,AGC ON), 0Lux with IR B&W: 0.001 Lux @(F1.6,AGC ON)
Electronic shutter speed	1s ~ 1/10000s
Main thread	25 fps (1920x1080)
Day/Night mode	Mechanical IR cut filter with auto-switching

Lens

Focal length	5–75 mm, 15x
Zoom	2.4s (optical Wide-Tele)
Lens viewing angle	Horizontal 53.8° - 4° Vertical 31.9° - 2.3° Diagonal 60.4° - 4.6°
Minimum working focusing distance	10 ~ 1500mm (Wide-Tele)
Diaphragm	F1.6 - F3.5
Focusing	Auto/ semi-automatic/ manual/region

Pan and tilt

Turning range	360°
Rotational speed	Manual: 0.1° - 80°/s, preset: 80°/s
Tilt range	-15° - 90° (auto-flip)
Tilt speed	Manual: 0.1° - 80°/s, preset: 80°/s
Presets	256
Patrols	10, up to 32 presets each
Templates	5 templates, total recording time no less than 10 minutes

Actions during downtime	Preset, Patrol, Pattern, Vertical Scan, Horizontal Scan, Panoramic Scan
Scheduled actions	Preset, Patrol, Pattern, Vertical Scan, Horizontal Scan, Panoramic Scan
Power-off memory	Supported

OSD menu

A.G.C.	Auto/manual
White balance	Auto/Manual/ATW/Indoor/Outdoor
Masking	8 areas
Image enhancement	WDR 120dB, BLC, 3D DNR, HLC, EIS

Interfaces

Video output	1 output switchable TVI/AHD/CVI/CVBS, BNC/ 1Vp-p composite (75 Ω/BNC)
RS-485	Half-duplex mode. Protocols: HIKVISION, Pelco-P, Pelco-D
UTC	HIKVISION_C

Basics

Nutrition	DC12V
Power consumption	20W max.
Working conditions	-40°C – 65°C, humidity no more than 90%
Protection	IP66 TVS 4000V Transient Voltage Suppressor for Lightning Protection
EXIR illumination range	Up to 100 m
EXIR illumination power	Automatically adjusts depending on zoom ratio
Housing material	Metal/plastic
Dimensions	Ø164.5 × 295 mm
Weight	2 kg

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az