

# DS-T215(C)

DS-T215(C) 5-75mm 2mp Optical Zoom 15X IR 100m HD Analog PTZ Kamera HiWatch



Model	DS-T215(C)
Brend	Hiwatch
Növ	Analoq
Meqapixel	2 MP
Obyektiv	PTZ
İşıqlandırma	İR
İşıqlandırma məsafəsi	100m
Qoruma	IP66
Material	Metal

## Specification

### Camera

Matrix	1/2.8 Progressive Scan CMOS
Number of effective pixels	1920x1080
Sensitivity	Color: 0.005Lux@(F1.6,AGC ON), 0Lux with IR B&W: 0.001 Lux @(F1.6,AGC ON)
Electronic shutter speed	1s ~ 1/10000s
Main thread	25 fps (1920x1080)
Day/Night mode	Mechanical IR cut filter with auto-switching

### Lens

Focal length	5-75 mm, 15x
Zoom	2.4s (optical Wide-Tele)
Lens viewing angle	Horizontal 53.8° - 4° Vertical 31.9° - 2.3° Diagonal 60.4° - 4.6°
Minimum working focusing distance	10 ~ 1500mm (Wide-Tele)
Diaphragm	F1.6 - F3.5
Focusing	Auto/ semi-automatic/ manual/region

### Pan and tilt

Turning range	360°
Rotational speed	Manual: 0.1° - 80°/s, preset: 80°/s

<b>Tilt range</b>	-15° - 90° (auto-flip)
<b>Tilt speed</b>	Manual: 0.1° - 80°/s, preset: 80°/s
<b>Presets</b>	256
<b>Patrols</b>	10, up to 32 presets each
<b>Templates</b>	5 templates, total recording time no less than 10 minutes
<b>Actions during downtime</b>	Preset, Patrol, Pattern, Vertical Scan, Horizontal Scan, Panoramic Scan
<b>Scheduled actions</b>	Preset, Patrol, Pattern, Vertical Scan, Horizontal Scan, Panoramic Scan
<b>Power-off memory</b>	Supported

## OSD menu

<b>A.G.C.</b>	Auto/manual
<b>White balance</b>	Auto/Manual/ATW/Indoor/Outdoor
<b>Masking</b>	8 areas
<b>Image enhancement</b>	WDR 120dB, BLC, 3D DNR, HLC, EIS

## Interfaces

<b>Video output</b>	1 output switchable TVI/AHD/CVI/CVBS, BNC/ 1Vp-p composite (75 Ω/BNC)
<b>RS-485</b>	Half-duplex mode. Protocols: HIKVISION, Pelco-P, Pelco-D
<b>UTC</b>	HIKVISION_C

## Basics

<b>Nutrition</b>	DC12V
<b>Power consumption</b>	20W max.
<b>Working conditions</b>	-40°C – 65°C, humidity no more than 90%
<b>Protection</b>	IP66 TVS 4000V Transient Voltage Suppressor for Lightning Protection
<b>EXIR illumination range</b>	Up to 100 m
<b>EXIR illumination power</b>	Automatically adjusts depending on zoom ratio
<b>Housing material</b>	Metal/plastic
<b>Dimensions</b>	Ø164.5 × 295 mm
<b>Weight</b>	2 kg