TP-LINK

EAP110-Outdoor

Kod: 00-00001635 · Access Pointlər



Tp-Link EAP110 - Outdoor xarici Wi-Fi tətbiqləri üçün IP65 hava şəraitinə davamlı poe access point.

Texniki göstəricilər

WiFi4
WIFI

2.4Ghz
Tezlik

PoE
PoE

Ətraflı məlumat

HARDWARE FEATURES	
Interface	1× Fast Ethernet (RJ-45) Port (Support Passive PoE)
Button	Reset
Power Supply	24V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)
Power Consumption	3.12 W
Dimensions (W x D x H)	8.5 × 1.8 × 1.1 in (216 × 46 × 27 mm)
Antenna Type	2× 3 dBi External Omni waterproof
Weatherproof Enclosure	IP65
Mounting	Pole / Wall Mounting (Kits included)

WIRELESS FEATURES	
Wireless Client Capacity	100+**
Wireless Standards	IEEE 802.11n/g/b
Frequency	2.4 GHz
Signal Rate	• 11n: Up to 300 Mbps (dynamic) • 11g: Up to 54 Mbps (dynamic) • 11b: Up to 11 Mbps (dynamic)
Transmit Power	• CE: ≤20 dBm (EIRP) • FCC: ≤22 dBm

WIRELESS FEATURES	
Wireless Functions	• Multiple SSIDs Up to 8 SSIDs • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control Adjust Transmit Power on dBm • QoS(WMM) • Load Balance • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	• Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK

MANAGEMENT	
Omada App	Yes
Centralized Management	• Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Cloud Access	Yes. Requiring the use of OC300, OC200, or Omada Software Controller.
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1, v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS

MANAGEMENT	
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes

OTHERS	
Certification	CE, FCC, RoHS
Package Contents	• 300Mbps Wireless N Outdoor Access Point, EAP110-Outdoor • Passive PoE Adapter • Power Cord • Mounting Kits • Waterproof Rubber Insert • Waterproof Antennas • Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Windows 11, Linux
Environment	• Operating Temperature: -30–65 ℃ (-22–149 ℉) • Storage Temperature: -40–70 ℃ (-40–158 ℉) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 239 59 10 · sales@eurotech.az