

EAP110-Outdoor

Tp-Link EAP110 - Outdoor xarici Wi-Fi tətbiqləri üçün IP65 hava şəraitinə davamlı poe access point.



| | |
|--------|----------------|
| Model | EAP110-Outdoor |
| Brend | Tp-Link |
| WIFI | WiFi4 |
| Tezlik | 2.4Ghz |
| PoE | PoE |

Specification

| HARDWARE FEATURES | |
|--------------------------|--|
| Interface | 1× Fast Ethernet (RJ-45) Port (Support Passive PoE) |
| Button | Reset |
| Power Supply | 24V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included) |
| Power Consumption | 3.12 W |
| Dimensions (W x D x H) | 8.5 × 1.8 × 1.1 in (216 × 46 × 27 mm) |
| Antenna Type | 2× 3 dBi External Omni waterproof |
| Weatherproof Enclosure | IP65 |
| Mounting | Pole / Wall Mounting (Kits included) |

| WIRELESS FEATURES | |
|--------------------------|---|
| Wireless Client Capacity | 100+** |
| Wireless Standards | IEEE 802.11n/g/b |
| Frequency | 2.4 GHz |
| Signal Rate | <ul style="list-style-type: none"> • 11n: Up to 300 Mbps (dynamic) • 11g: Up to 54 Mbps (dynamic) • 11b: Up to 11 Mbps (dynamic) |
| Transmit Power | <ul style="list-style-type: none"> • CE: ≤20 dBm (EIRP) • FCC: ≤22 dBm |

| WIRELESS FEATURES | |
|--------------------|---|
| Wireless Functions | <ul style="list-style-type: none"> • Multiple SSIDs: Up to 8 SSIDs • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control: Adjust Transmit Power on dBm • QoS(WMM) • Load Balance • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client |
| Wireless Security | <ul style="list-style-type: none"> • Captive Portal Authentication • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support • 64/128/152-bit WEP / WPA / WPA2-Enterprise, WPA-PSK / WPA2-PSK |

| MANAGEMENT | |
|------------------------------------|---|
| Omada App | Yes |
| Centralized Management | <ul style="list-style-type: none"> • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller |
| Cloud Access | Yes. Requiring the use of OC300, OC200, or Omada Software Controller. |
| Email Alerts | Yes |
| LED ON/OFF Control | Yes |
| Management MAC Access Control | Yes |
| SNMP | v1, v2c |
| System Logging Local/Remote Syslog | Local/Remote Syslog |
| SSH | Yes |
| Web-based Management | HTTP/HTTPS |
| L3 Management | Yes |
| Multi-site Management | Yes |
| Management VLAN | Yes |

| OTHERS | |
|---------------------|--|
| Certification | CE, FCC, RoHS |
| Package Contents | <ul style="list-style-type: none"> • 300Mbps Wireless N Outdoor Access Point, EAP110-Outdoor • Passive PoE Adapter • Power Cord • Mounting Kits • Waterproof Rubber Insert • Waterproof Antennas • Installation Guide |
| System Requirements | Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows 10, Windows 11, Linux |
| Environment | <ul style="list-style-type: none"> • Operating Temperature: -30~65 ℃ (-22~149 ℉) • Storage Temperature: -40~70 ℃ (-40~158 ℉) • Operating Humidity: 10~90% RH non-condensing • Storage Humidity: 5~90% RH non-condensing |