

EAP115

TP-link EAP115 300MBPS WIRELESS N CEILING MOUNT ACCESS POINT, WIFI4 PoE



Model	EAP115
Brend	Tp-Link
Tezlik	2.4Ghz
PoE	PoE
WIFI	WiFi4
Qoşulma sayı	100+

Specification

HARDWARE FEATURES	
Interface	Fast Ethernet (RJ-45) Port *1 Support IEEE802.3af PoE
Physical Security Lock	Kensington Lock Slot
Button	Reset
Power Supply	PoE or external 12VDC/1.0A power supply
Power Consumption	5W
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Dimensions (W x D x H)	7.1 x 7.1 x 1.9 in. (180*180*47.5mm)
Antenna Type	Internal 2* 3dBi Omni
Mounting	Ceiling /Wall Mounting (Kits included)
Watch Dog	Yes
WIRELESS FEATURES	
Wireless Client Capacity	100+**
Wireless Standards	IEEE 802.11n, IEEE 802.11g, IEEE 802.11b
Frequency	2.4-2.4835GHz
Signal Rate	11n: Up to 300Mbps(dynamic) 11g: Up to 54Mbps(dynamic) 11b: Up to 11Mbps(dynamic)
Reception Sensitivity	300M: -71dBm@10% PER 150M: -75dBm@10% PER 54M: -78dBm@10% PER 11M: -93dBm@8% PER 6M: -92dBm@10% PER 1M: -96dBm@8% PER

HARDWARE FEATURES	
Wireless Functions	Multiple SSIDs (Up to 8 SSIDs) Enable/Disable Wireless Radio Automatic Channel Assignment Transmit Power Control (Adjust Transmit Power on dBm) QoS(WMM) Rate Limit Reboot Schedule Wireless Schedule Wireless Statistics based on SSID/AP/Client
Wireless Security	Captive Portal Authentication Access Control Wireless Mac Address Filtering Wireless Isolation Between Clients SSID to VLAN Mapping Rogue AP Detection 802.1X Support 64/128/152-bit WEP / WPA / WPA2-Enterprise,WPA-PSK / WPA2-PSK
Transmission Power	CE: <20dBm FCC: <26dBm
MANAGEMENT	
Omada App	Yes
Auranet Controller Software	Yes
Centralized Management	<ul style="list-style-type: none"> • Omada Hardware Controller (OC300) • Omada Hardware Controller (OC200) • Omada Software Controller
Cluster Mode	Yes
Cloud Access	Yes (Through OC300, OC200, or Omada Software Controller)
EAP Controller Software	
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1,v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
OTHERS	
Certification	CE, FCC, RoHS
Package Contents	300Mbps Wireless N Ceiling Mount Access Point EAP115 Power Adapter Mounting Kits, Installation Guide
System Requirements	Microsoft Windows 10/8/7/Vista/XP
Environment	Operating Temperature: 0~40 (32~104) Storage Temperature: -40~70 (-40~158) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~90% non-condensing