

EAP211-BRIDGE KIT

"TP-Link EAP211-Bridge KIT – 5GHz tezlikdə 867Mbps sürət, daxili və açıq hava üçün uyğun dizayn ilə uzaq məsafəli simsiz bağlantılar üçün ideal Wi-Fi həlli.



Specifications

Model	EAP211-Bridge KIT
Brand	Tp-Link
WIFI	WiFi5
Tezlik	5Ghz
PoE	PoE

KEY FEATURES

HARDWARE FEATURES	
Interface	3x Gigabit Ethernet Ports
Button	Reset
DIP Switch	Role Switch
Power Supply	12V DC / 802.3af PoE / 24V Passive PoE
Max. Power Consumption	11.5W
Dimensions (W x D x H)	3.1 × 2.4 × 8.8 in (79 × 60 × 224 mm)
Antenna	Internal 2×2 Dual-polarized directional MIMO antennas 5 GHz: 10.0 dBi Horizontal:60°, Vertical: 30°
Weatherproof Enclosure	IP65
Mounting	Pole and wall mounting (Pole accessories included)
WIRELESS FEATURES	
Coverage	1000m(3280ft)*
Wireless Standards	IEEE 802.11 a/n/ac
Frequency	5 GHz
Signal Rate	5 GHz: Up to 867 Mbps§
Wireless Functions	• MU-MIMO: 5G 2x2 MU-MIMO DL • Multiple SSIDs:8 • Wireless Statistics • Wireless Schedule • Reboot Schedule • RADIUS Accounting • Static IP/Dynamic IP • Rate Limit • Guest Network • Enable/Disable Wireless Radio • Enable/Disable SSID Broadcast
Wireless Security	• VLAN • Rogue AP Detection • Maximum number of MAC Filter: 4,000 • Wireless Encryption • CE: <23dBm (5 GHz, band 1/2, EIRP); <30dBm (5 GHz, band3, EIRP)
Transmission Power	• FCC: <23dBm (5 GHz, band1) <25dBm (5 GHz, band4)
Management Features	
Omada App	Yes
Restore & Backup	Yes
Firmware update via Web	Yes
NTP	Yes

HARDWARE FEATURES

Centralized Management	• Omada Hardware Controller • Omada Software Controller • Omada Cloud-Based Controller • Omada App
Cloud Access	Yes. Require the use of Omada Controllers.
Email Alerts	Yes
LED ON/OFF Control	Yes
SNMP	Yes
SSH	Yes
Web-based Management	Yes
Zero-Touch Provisioning	Yes
OTHERS	
Certification	CE, FCC, RoHS
Package Content	• EAP211-Bridge KIT • Installation Guide • Mounting Kit
Lightning Protection	• Air discharge: ±8kV • Contact discharge: ±4kV • Common mode 10/700: ±6kV
Environment	• Operating Temperature: -40 °C–70 °C (-40 °F–158 °F); • Storage Temperature: -40 °C–70 °C (-40 °F–158 °F); • Operating Humidity: 10%–90% non-condensing; • Storage Humidity: 5%–90% non-condensing