

EAP225

Tp-Link EAP225 access point 2.4 GHz-də 450 Mbps və 5 GHz-də 867 Mbps cəmi 1317 Mbps Wi-Fi sürətidir.



Model	EAP225
Brend	Tp-Link
WIFI	WiFi5
Tezlik	2.4Ghz/5Ghz
PoE	PoE
Genişlik	Dual band

Specification

HARDWARE FEATURES	
Interface	Gigabit Ethernet (RJ-45) Port×1 (Support IEEE802.3af/at PoE and Passive PoE)
Physical Security Lock	Yes
Button	Reset
Power Supply	• 802.3af/at PoE • 48V Passive PoE (+4,5pins; -7,8pins. PoE Adapter Included)
Power Consumption	EU: 9.7W US: 12.1W
Dimensions (W x D x H)	8.1 × 7.1 × 1.5 in (205.5 × 181.5 × 37.1 mm)
Antenna Type	3 Internal Omni • 2.4 GHz: 4 dBi • 5 GHz: 5 dBi
Mounting	Ceiling /Wall Mounting (Kits included)

WIRELESS FEATURES	
Wireless Client Capacity	220+**
Wireless Standards	IEEE 802.11ac/n/g/b/a
Frequency	2.4 GHz and 5 GHz
Signal Rate	• 5 GHz:Up to 867 Mbps • 2.4 GHz:Up to 450 Mbps

WIRELESS FEATURES	
Wireless Functions	<ul style="list-style-type: none"> • Multiple SSIDs (Up to 15 SSIDs, 8 for 2.4GHz band,7 for 5GHz band) • Enable/Disable Wireless Radio • Automatic Channel Assignment • Transmit Power Control (Adjust Transmit Power on dBm) • QoS(WMM) • Seamless Roaming* • Omada Mesh* • Band Steering • Load Balance • MU-MIMO • Airtime Fairness • Beamforming • Rate Limit • Reboot Schedule • Wireless Schedule • Wireless Statistics based on SSID/AP/Client
Wireless Security	<ul style="list-style-type: none"> • Captive Portal Authentication* • Access Control • Wireless Mac Address Filtering • Wireless Isolation Between Clients • SSID to VLAN Mapping • Rogue AP Detection • 802.1X Support
Transmission Power	<ul style="list-style-type: none"> • CE: <ul style="list-style-type: none"> ≤20 dBm(2.4 GHz, EIRP) ≤23 dBm(5 GHz, EIRP) • FCC: <ul style="list-style-type: none"> ≤24 dBm(2.4 GHz) ≤22 dBm(5 GHz)

MANAGEMENT	
Omada App	Yes
Centralized Management	<ul style="list-style-type: none"> • Omada Hardware Controller OC300 • Omada Hardware Controller OC200 • Omada Software Controller • Omada Cloud-Based Controller (Supported by EAP225 V3.0, V4.0 and above, and is not supported by EAP225 V3.20)
Cloud Access	Yes, through <ul style="list-style-type: none"> • OC300 • OC200 • Omada Software Controller • Omada Cloud-Based Controller (Supported by EAP225 V3.0, V4.0 and above, and is not supported by EAP225 V3.20)
Email Alerts	Yes
LED ON/OFF Control	Yes
Management MAC Access Control	Yes
SNMP	v1,v2c
System Logging Local/Remote Syslog	Local/Remote Syslog
SSH	Yes
Web-based Management	HTTP/HTTPS
L3 Management	Yes
Multi-site Management	Yes
Management VLAN	Yes
Zero-Touch Provisioning	Yes. Requiring the use of Omada Cloud-Based Controller (Supported by EAP225 V3.0, V4.0 and above, and is not supported by EAP225 V3.20)

OTHERS	
Certification	CE, FCC, RoHS
Package Contents	<ul style="list-style-type: none"> • AC1350 Wireless MU-MIMO Gigabit Ceiling Mount Access Point EAP225 • Passive PoE Adapter • Power Cord • Mounting Kits • Installation Guide
System Requirements	Microsoft Windows XP, Vista, Windows 7, Windows 8, Windows10, Windows11, Linux
Environment	<ul style="list-style-type: none"> • Operating Temperature: 0–40 ℃ (32–104 ℉) • Storage Temperature: -40–70 ℃ (-40–158 ℉) • Operating Humidity: 10–90% RH non-condensing • Storage Humidity: 5–90% RH non-condensing