GENATA

GNT-IG1210FP-AC

Kod: 00-00004884 · Switchlər



GNT-IG1210FP-AC ndustrial 8 Port Full Gigabit Unmanaged PoE Switch Genata

Texniki göstəricilər

8 Port
Port sayı

PoE
PoE

1000mb/s
Port sürəti

120 W
PoE gücü

Ətraflı məlumat

Model	GNT-IG1210FP-AC
Ports	PoE (1~6):10/100/1000Mbps PoE ports (RJ45), PoE (7~8):10/100/1000Mbps PoEports (RJ45),Support bt 60W HighPower SFP(1~2):10/100/1000Mbps SFP ports
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:20Gbps
	Network Latency (10 to 1000Mbps): ≦16μs (usethe 64byte packagesize)
	MAC address table: 8K
	Packet forwarding rate: 14.88Mpps
	The Frame Filter& Transmission Rate:14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i10BASE-T/IEEE 802.3u 100BASE-TX
	IEEE 802.3ab 1000BASE-T
	IEEE 802.3xFlow Control
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power Input:90~264VAC, DC48-52V input,Triple Redundancy, Total≤130W AI Watchdog: Port 1~8 Power Output:PoE1~6 Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Protection Level:IP40, Lightning Protection:6KV, ESD Protection:8KV, IEC61000-4-5 Surge Protection 6KV, IEC61000-4-2 ESD 8/15KV
Physical Specifications	Size(H*D*W): 145*110*88mm, Weight: 0.9KG/Pcs
Package	Size(L*W*H): 400*360*230mm(CTN Box); 12Pcs/CTN

Working Environment	Operating Temperature: -40°C~70°C
	Storage Temperature: -40°C~70°C
	Relative Humidity: 5%~90% Non-condensing
	Heat dissipation mode: fanless design, natural heat dissipation
Certification	CE Mark
	FCC Part15,Class B
	RoHS 2.0
Warranty	Whole Device:1 year
Package Content	User Manual,Terminal

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az