

# GNT-IG1210FP-AC

GNT-IG1210FP-AC Industrial 8 Port Full Gigabit Unmanaged PoE Switch



Model	GNT-IG1210FP-AC
Brend	Genata
PoE gücü	120 W
Port sayı	8 Port
PoE	PoE
Port sürati	1000mb/s

## Specification

Model	GNT-IG1210FP-AC
Ports	PoE (1~6):10/100/1000Mbps PoE ports (RJ45), PoE (7~8):10/100/1000Mbps PoEports (RJ45),Support bt 60W HighPower SFP(1~2):10/100/1000Mbps SFP ports
Transmission Rate	2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex
Transmission Distance	130m
Performance Specification	Bandwidth:20Gbps Network Latency (10 to 1000Mbps): ≤16µs (usethe 64byte packagesize) MAC address table: 8K Packet forwarding rate: 14.88Mpps The Frame Filter& Transmission Rate:14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port
Networking Standard	IEEE 802.3i10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3xFlow Control IEEE 802.3af/at/bt Power over Ethernet

<b>Power Support</b>	<p>Power Input:90~264VAC, DC48-52V input, Triple Redundancy, Totals130W</p> <p>AI Watchdog: Port 1~8</p> <p>Power Output:PoE1~6 Port:1/2(+52V),3/6(GND)≤30W</p> <p>PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W</p>
<b>Protection Level</b>	<p>Protection Level:IP40, Lightning Protection:6KV, ESD Protection:8KV,</p> <p>IEC61000-4-5 Surge Protection 6KV, IEC61000-4-2 ESD 8/15KV</p>
<b>Physical Specifications</b>	Size(H*D*W): 145*110*88mm, Weight: 0.9KG/Pcs
<b>Package</b>	Size(L*W*H): 400*360*230mm(CTN Box); 12Pcs/CTN
<b>Working Environment</b>	Operating Temperature: -40°C~70°C
	Storage Temperature: -40°C~70°C
	Relative Humidity: 5%~90% Non-condensing
	Heat dissipation mode: fanless design, natural heat dissipation
<b>Certification</b>	CE Mark
	FCC Part15,Class B
	RoHS 2.0
<b>Warranty</b>	Whole Device:1 year
<b>Package Content</b>	User Manual,Terminal