
GENATA

# GNT-P1012G6-F

Kod: 00-00004886 · Switchlər



GNT-P1012G6-F 8pGb +2SFP AI Gigabit Waterproof PoE Switch Genata

## Texniki göstəricilər

**8 Port**
Port sayı

**PoE**
PoE

**1000mb/s**
Port sürəti

**120 W**
PoE gücü

## Ətraflı məlumat

| GNT-P1012G6 | Product Features |
|---|---|
| Total 120W PowerSupply 8 ports PoE<br>2 ports Uplink<br>2 ports SFP | AI Watchdog Function<br>6KV Lightning &8KV ESD Protection Support bt 60W High Power |
| **Specifications** | |
| Ports | PoE (1~6):10/100/1000Mbps PoE ports (RJ45)<br>PoE (7~8):10/100/1000Mbps PoE ports (RJ45),Support bt 60W<br>High Power LAN (1~2):10/100/1000Mbps uplink ports (RJ45)<br>SFP (1~2):10/100/1000Mbps SFP ports |
| Transmission Rate | 2000Mbps Full Duplex; 10 or 100 or 1000 Mbps HalfDuplex |
| Transmission Distance | 130m |
| Performance Specification | Bandwidth:24Gbps<br>NetworkLatency (10 to 1000Mbps): 16μs(use the 64bytepackage size) MAC address table: 8K<br>The Frame Filter& Transmission Rate:14800pps the mostfor 10M port,<br>148800pps the mostfor 100M port;1488000pps the most for1000M port |
| Networking Standard | IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T<br>IEEE 802.3x FlowControl<br>IEEE 802.3af/at/bt Powerover Ethernet |
| Power Support | Power Input: AC 90~240VTotal≤120W<br>AI Watchdog: Port1~8<br>Power Output: PoE1~6Port:1/2(+52V),3/6(GND)≤30W<br>PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W |
| Protection Level | Lightning Protection:6KV, Per: IEC61000-4-5<br>ESD Protection:8KV, Per: IEC61000-4-2 |

| | |
|---|---|
| Physical Specifications | Size(L*W*H): 187mm*139mm*43mm, Weight:1.0KG |
| Working Environment | OperatingTemperature: -30℃~60℃ Storage Temperature: -40℃~70℃<br>Operating Humidity: 10%~90% Non-condensing<br>Storage Humidity: 5%~90% Non-condensing |
| Certification | CEMark<br>FCC Part15, ClassB RoHS 2.0 |
| Package Content | AC Power Cable,User Manual |

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az