

GNT-P1210SG

GNT-P1210SG 8p 2 Up-link AI Hybrid PoE Switch Genata



| | |
|-------------|-------------|
| Model | GNT-P1210SG |
| Brend | Genata |
| PoE gücü | 120 W |
| Port sayı | 8 Port |
| PoE | PoE |
| Port sürati | 100mb/s |

Specification

| | |
|------------------------------------|---|
| GNT-P1210SG | Product Features |
| Total 120W PowerSupply 8 ports PoE | AI Watchdog Function |
| 2 ports Uplink | 6KV Lightning & 8KVESD Protection Support bt 60W High Power |
| Specifications | |
| Ports | PoE (1~6):10/100Mbps PoE ports(RJ45) PoE (7~8):10/100Mbps PoE ports (RJ45),Support bt 60W High Power LAN (1~2):10/100/1000Mbps uplink ports (RJ45) |
| Transmission Rate | 2000Mbps Full Duplex; 10 or 100 or 1000 Mbps HalfDuplex |
| Transmission Distance | 130m |
| Performance Specification | Bandwidth:5.6Gbps NetworkLatency (10 to 1000Mbps): 16μs(use the 64bytepackage size) MAC address table: 8K The Frame Filter& Transmission Rate:14800pps the mostfor 10M port, 148800pps the mostfor 100M port;1488000pps the most for1000M port |
| Networking Standard | IEEE 802.3i 10BASE-T/IEEE 802.3u 100BASE-TX IEEE 802.3ab 1000BASE-T IEEE 802.3x FlowControl IEEE 802.3af/at/bt Powerover Ethernet |

| | |
|--------------------------------|--|
| Power Support | Power Input: AC 90~240V Totals120W AI Watchdog: Port1~8 Power Output: PoE1~6Port:1/2(+52V),3/6(GND)≤30W PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W |
| Protection Level | Lightning Protection:6KV, Per:IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2 |
| Physical Specifications | Size(L*W*H): 187mm*139mm*43mm, Weight:1.0KG |
| Working Environment | OperatingTemperature: -30~60 Storage Temperature: -40~70 Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing |
| Certification | CE Mark FCC Part15, Class B RoHS 2.0 |
| Package Content | AC Power Cable,User Manual |