

# GNT-P4804F6

GNT-P4804F6 6pMb 2pGb +2SFP AI Waterproof PoE Switch Genata



## Specifications

Model	GNT-P4804F6
Brand	Genata
PoE gücü	120 W
Port say?	8 Port
PoE	PoE
Port sür?ti	100mb/s

KEY FEATURES

<b>Model</b>	<b>GNT-P4804F6</b>
<b>Ports</b>	<p>PoE (1~6):10/100Mbps PoE ports (RJ45)</p> <p>PoE (7~8):10/100/1000Mbps PoE ports (RJ45),Support bt 60W HighPower LAN(1~2):10/100/1000Mbps uplink ports (RJ45)</p> <p>SFP:10/100/1000Mbps SFP port</p>
<b>Transmission Rate</b>	<b>2000Mbps FullDuplex; 10 or 100 or 1000 MbpsHalf Duplex</b>
<b>Transmission Distance</b>	<p><b>130m</b></p> <p><b>Bandwidth:11.2Gbps</b></p> <p><b>Network Latency(10 to 1000Mbps): ≤16μs (usethe 64byte packagesize)</b></p> <p><b>MAC address table: 8K</b></p>
<b>Performance Specification</b>	<p><b>The FrameFilter &amp; Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port;1488000pps the most for 1000M port</b></p> <p><b>IEEE 802.3i 10BASE-T/IEEE 802.3u100BASE-TX</b></p> <p><b>IEEE 802.3ab 1000BASE-T</b></p> <p><b>IEEE 802.3x Flow Control</b></p>
<b>Networking Standard</b>	<p><b>IEEE 802.3af/at/bt Power over Ethernet</b></p> <p><b>Power Input:AC 90~240V Total≤120W</b></p>
<b>Power Support</b>	<p><b>AI Watchdog: Port 1~8</b></p> <p><b>Power Output:PoE1~6 Port:1/2(+52V),3/6(GND)≤30W</b></p> <p><b>PoE7~8 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W</b></p>
<b>Protection Level</b>	<b>Lightning Protection:6KV ESD Protection:8KV</b>
<b>Physical Specifications</b>	<p><b>Size(L*W*H): 310mm*260mm*100mm, Weight:1.6KG</b></p> <p><b>Operating Temperature: -30°C~60°C</b></p> <p><b>Storage Temperature: -40°C~70°C</b></p>
<b>Working Environment</b>	<p><b>Operating Humidity: 10%~90% Non-condensing</b></p> <p><b>Storage Humidity: 5%~90% Non-condensing</b></p> <p><b>CE Mark</b></p> <p><b>FCC Part15,Class B</b></p>
<b>Certification</b>	<b>RoHS 2.0</b>

---

Warranty

Whole Device:1 year

Package Content

AC Power Cable,User Manual