GENATA

GNT-P9206EA

Kod: 00-00004892 · Switchlər



GNT-P9206EA 4p 2Up-Link 250m AI PoE Switch Genata

Texniki göstəricilər

5 Port	Port sayı
PoE	PoE
100mb/s	Port sürəti
60 W	PoE gücü

Ətraflı məlumat

GNT-P9206EA	Product Features
Total 65W PowerSupply 4 ports PoE 2 ports Uplink	AI Watchdog Function 6KV Lightning &8KV ESD Protection Support bt 60W High Power Auto-Adaption 250m Transmission
Specifications	
Ports	PoE (1~3):10/100Mbps PoE ports(RJ45) PoE (4):10/100Mbps PoE port (RJ45),Support bt 60W High Power LAN (1~2):10/100Mbps uplink ports (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100MbpsHalf Duplex
Transmission Distance	100Mbps /10Mbps, Auto-Adaption 250m
Performance Specification	Bandwidth:1.2Gbps Network Latency (10 to 100Mbps): <= 16μs (use the 64bytepackage size) MAC address table: 2K The Frame Filter& Transmission Rate:14800pps the mostfor 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T IEEE 802.3u 100BASE-TX IEEE 802.3x FlowControl IEEE 802.3af/at/bt Powerover Ethernet
Power Support	Power Input: AC 90~240VTotal≤65W AI Watchdog: Port1~4 Power Output: PoE1~3Port:1/2(+52V),3/6(GND)≤30W PoE 4 Port:1245(+53V),3678(GND) Compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV, Per:IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Physical Specifications	Size(L*W*H): 187mm*139mm*43mm, Weight:1.0KG

Working Environment	OperatingTemperature: -30℃~60℃ Storage Temperature: -40℃~70℃ Operating Humidity: 10%~90% Non-condensing Storage Humidity: 5%~90% Non-condensing
Certification	CEMark FCC Part15, ClassB RoHS 2.0
Package Content	AC Power Cable,User Manual

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az