GENATA

GNT-P9206EB

Kod: 00-00004889 · Switchlər



GNT-P9206EB 4p 2Up-Link 130m AI PoE Switch Genata

Texniki göstəricilər

5 Port
Port sayı

PoE
PoE

100mb/s
Port sürəti

60 W
PoE gücü

Ətraflı məlumat

Ports	PoE (1~3) :10/100Mbps PoE ports (RJ45) PoE (4) :10/100Mbps PoE port,BT port, Compatible uplink port (RJ45) LAN (1~2):10/100Mbps uplink port (RJ45)
Transmission Rate	200Mbps Full Duplex; 10 or 100 Mbps Half Duplex
Transmission Distance	100Mbps /10Mbps Adaptive MAX 250m
Performance Specification	Bandwidth: 1.2Gbps
	Network Latency (10 to 1000Mbps): 16μs (use the 64byte package size)
	MAC address table: 2K
	The Frame Filter & Transmission Rate: 14800pps the most for 10M port, 148800pps the most for 100M port
Networking Standard	IEEE 802.3i 10BASE-T
	IEEE 802.3u 100BASE-TX
	IEEE 802.3xFlowControl
	IEEE 802.3af/at/bt Power over Ethernet
Power Support	Power input: AC 110~220V Total≤65W PoE Watchdog: Port 1~4 Power output: PoE1~3Port:1/2(+52V),3/6(GND)≤30W PoE 4 Port:1245(+53V),3678(GND) compatible1/2(+52V),3/6(GND)≤60W
Protection Level	Lightning Protection:6KV, Per: IEC61000-4-5 ESD Protection:8KV, Per: IEC61000-4-2
Package Size	Size(L*W*H):187mm*139mm*43mm
Working Environment	Operating Temperature: -30℃ ~60℃
	Storage Temperature: -40℃ ~70℃
	Operating Humidity: 10%~90% non-condensing
	Storage Humidity: 5%~90% non-condensing

Electromagnetic Compatibility	CE mark
	FCCPart15,Class B
	VCCI ClassBEN55022 (CISPR 22)
	C-Tick
Warranty	Whole device: 1 year
Package Content	Installation Manual

Sənəd avtomatik yaradılıb. Qiymət və mövcudluq üçün bizimlə əlaqə saxlayın — +994 10 228 00 16 · sales@eurotech.az